


1 LOCATION OF WATER WELL:		Fraction <u>SE 1/4 SW 1/4 NE 1/4</u>		Section Number <u>15</u>		Township Number <u>24</u> S		Range Number <u>2</u> E																																																	
County: <u>HARVEY</u> Distance and direction from nearest town or city street address of well if located within city? <u>5 1/2 No Bentley KS 1/4 West.</u>																																																									
2 WATER WELL OWNER: <u>Ed. Preher</u> RR#, St. Address, Box # : <u>R# Halstead KS 67056</u> City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:																																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>42</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>42</u> ft. below land surface measured on mo/day/yr <u>12-4-89</u> Pump test data: Well water was <u>42</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm Est. Yield <u>80</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>11</u> in. to <u>80</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No																																																						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter <u>5</u> in. to <u>6.5</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>12</u> in., weight <u>11.59</u> lbs./ft. Wall thickness or gauge <u>SRR-26</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>6.5</u> ft. to <u>80</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>80</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>23</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>West.</u> How many feet? <u>17.5</u>																																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>2</td> <td>Top soi.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>18</td> <td>clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18</td> <td>34</td> <td>fine SAND.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>34</td> <td>35</td> <td>clay.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>35</td> <td>57</td> <td>fine sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>57</td> <td>62</td> <td>clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>62</td> <td>80</td> <td>fine to med sand</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2	Top soi.				2	18	clay				18	34	fine SAND.				34	35	clay.				35	57	fine sand				57	62	clay				62	80	fine to med sand			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																				
0	2	Top soi.																																																							
2	18	clay																																																							
18	34	fine SAND.																																																							
34	35	clay.																																																							
35	57	fine sand																																																							
57	62	clay																																																							
62	80	fine to med sand																																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-4-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>12-5-89</u> under the business name of <u>Wenger Pully</u> by (signature) <u>[Signature]</u>																																																									