

WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SW 1/4 SW 1/4	22	T 24 S	R 2 W
Distance and direction from nearest town or city street address of well if located within city?					
4 mi. S + 1 mi. W of Halstead, Ks.					
WATER WELL OWNER: James Fein					
RR#, St. Address, Box #: RR 2					
City, State, ZIP Code: Halstead, Ks. 67056					
Board of Agriculture, Division of Water Resources					
Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 112 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 37 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 37 ft. below land surface measured on mo/day/yr 5-3-83			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10-15 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 167 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		2 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter 5 in. to 102 ft. Dia		in. to ft. Dia in. to ft.			
Casing height above land surface 12 in. weight 2.91 lbs./ft. Wall thickness or gauge No. 26.5					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 102 ft. to 112 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 15 ft. to 112 ft. From ft. to ft.			
GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 5 ft. to 15 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 100			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 3 Top Soil		153 16507 Fine Sand			
3 7 01 Grey Clay		165 16701 Grey clay			
7 2304 Red Sandy Clay					
23 2507 Fine brown sand					
25 280 Grey Sandy clay					
28 3404 Sandy clay					
34 6805 Fine to med brown sand					
68 7411 Coarse gravel					
74 7501 Brown clay					
75 96 Med grey sand					
96 11308 Med tan sand					
113 14601 Brown tan grey clay					
146 14907 Fine Sand					
149 15301 Grey Clay					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-83 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 6-29-83					
Under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

DP