

26w191 mw-19

WATER WELL RECORD

Form WWC-5


KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	<u>SE 1/4 SE 1/4 NE 1/4</u>	<u>2</u>	T <u>24</u> S	R <u>2</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

1/2 SW of 10th St. & McNaair, Halstead

2 WATER WELL OWNER: <u>Legg Company, Inc.</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>325 E. 10th Street</u>	Application Number:
City, State, ZIP Code: <u>Halstead, KS 67056</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>37.0</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>18.86</u> ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter in. to ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>2</u> in. to <u>27</u> ft. Dia			<u>Threaded</u> <u>flush</u>
Casing height above land surface <u>flush</u> in. weight <u>0.703</u> lbs./ft. Wall thickness or gauge No. <u>sch 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>Mill slot</u>	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:	From <u>27</u> ft. to <u>37</u> ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From <u>24</u> ft. to <u>37</u> ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals: From <u>3</u> ft. to <u>24</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage				

Direction from well?		How many feet?	
FROM	TO	FROM	TO
0	18		
18	20		
20	24		
24	35.5		
35.5	37		
LITHOLOGIC LOG		PLUGGING INTERVALS	
Silty clay			
Sandy clay			
Clayey sand			
Sand, f-c grained			
Silty clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-1-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>9-14-98</u> under the business name of <u>Geotechnical Services, Inc. (GSI)</u> by (signature) <u>Allison M. Shiver</u>
