

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Harvey		NW 1/4 NW 1/4 NW 1/4		1		T 24 S		R 2 E (W)	

Distance and direction from nearest town or city street address of well if located within city?

Just east of Halstead

2 WATER WELL OWNER:		City of Wichita		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #		: 455 N. Main		Application Number:	
City, State, ZIP Code		Wichita, KS 67202			

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 42 ft. ELEVATION: unknown	
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL not checked ft. below land surface measured on mo/day/yr Pump test data: Well water was not checked ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 41 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Index Well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒	

5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded	
(2) PVC 4 ABS		7 Fiberglass Threaded	
Blank casing diameter 2 in. to 20 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface 24 in., weight .70 lbs./ft. Wall thickness or gauge No .154	
TYPE OF SCREEN OR PERFORATION MATERIAL:		(7) PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 15 ft. to 41 ft., From ft. to ft.	

6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug	
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 15 ft.		What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		None known	
Direction from well?		How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	19	Clay, brownish gray			
19	32	Sand and gravel, medium, fine			
32	41	Clay, green gray, gravel streaks			
		<i>SPECIAL Construction</i>			
		<i>INDEX WELL</i>			
		<i>GHQ # 2</i>			
		<i>USGS</i>			
		<i>1</i>			
		<i>CITY OF WICHITA</i>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-14-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 9-20-01 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>	
---	--