

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Harvey	SE 1/4 SE 1/4 SW 1/4	22	T 24 S	R 2 E (W)

Distance and direction from nearest town or city street address of well if located within city?
Approximately 4 miles south and 1/2 mile west of Halstead

2 WATER WELL OWNER:	City of Wichita	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #	: 455 N. Main	Application Number: HV006
City, State, ZIP Code	: Wichita, KS 67202	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	190.78	ft.	ELEVATION:	unknown			
	Depth(s) Groundwater Encountered	1	ft.	2	ft.	3	ft.	
	WELL'S STATIC WATER LEVEL	30	ft. below land surface measured on	mo/day/yr	9-20-01			
	Pump test data: Well water was	not checked	ft. after		hours pumping		gpm	
	Est. Yield	unknown	gpm: Well water was		ft. after		hours pumping	gpm
	Bore Hole Diameter	42	in. to	191	ft., and		in. to	ft.
	WELL WATER TO BE USED AS:	(5) Public water supply	8 Air conditioning	11 Injection well				
	1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (specify below)			
	2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	10 Monitoring well				
	Was a chemical/bacteriological sample submitted to Department?	Yes	No	✓	If yes, mo/day/yr sample was sub-			
	mitted				Water Well Disinfected?	Yes	✓	No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped			
(1) Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	✓		
2 PVC	4 ABS	7 Fiberglass		Threaded			
Blank casing diameter	18	in. to	120.55	ft., Dia		in. to	ft.
Casing height above land surface	21	in., weight	70.59	lbs./ft. Wall thickness or gauge No	.375		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement					
1 Steel	(3) Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)				
(1) Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes				
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)				
SCREEN-PERFORATED INTERVALS:	From	120.55	ft. to	189	ft., From	ft. to	ft.
	From		ft. to		ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	From	21	ft. to	191	ft., From	ft. to	ft.
	From		ft. to		ft., From	ft. to	ft.

6 GROUT MATERIAL:	1 Neat cement	(2) Cement grout	3 Bentonite	4 Other				
Grout Intervals: From	0	ft. to	21	ft., From	ft. to	ft., From	ft. to	ft.
What is the nearest source of possible contamination:								
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well				
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well				
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)				
			13 Insecticide storage	None known				
Direction from well?			How many feet?					

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	19	Clay, brown			
19	41	Sand and gravel, fine, medium			
41	44	Clay			
44	88	Sand and gravel, fine, medium, some clay			
88	122	Clay			
122	155	Sand and gravel, fine, medium, some clay			
155	166	Clay			
166	176	Sand and gravel, fine, medium with clay			
176	181	Clay			
181	189	Sand and gravel, fine, medium			
189	191	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was	(1) constructed	(2) reconstructed	or	(3) plugged	under my jurisdiction and was
completed on (mo/day/year)	9-20-01					and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No	185	This Water Well Record was completed on (mo/day/yr)	9-26-01			
under the business name of	Clarke Well & Equipment, Inc.	by (signature)				