


1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County:	<i>Harvey</i>	<i>NE 1/4 NE 1/4 NE 1/4</i>	<i>2</i>	T <i>24</i> S	R <i>2</i> E <i>W</i>

Distance and direction from nearest town or city street address of well if located within city?
616 Walnut in Halstead

2 WATER WELL OWNER: Ryan Speer		Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # :	616 Walnut	
City, State, ZIP Code :	Halstead, KS 67056	

3	LOCATE WELL'S LOCATION WITH	4	DEPTH OF COMPLETED WELL <u>92</u> ft. ELEVATION:
---	-----------------------------	---	--

AN "X" IN SECTION BOX:



Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL .. 2.0 ft. below land surface measured on mo/day/yr. 5-30-07

Pump test data: Well water was 2.3 ft. after 1/2 hours pumping 3.0 gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	<u>①</u> Domestic (lawn & garden)	12 Other (Specify below)
	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? (Yes) No

5	TYPE OF BLANK CASING USED:			3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped	
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded		
	② PVC	4 ABS	7 Fiberglass	Threaded		
Blank casing diameter <u>5</u> in. to <u>8.2</u> ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface <u>12</u> in., weight <u>2.29</u> lbs./ft. Wall thickness or guage No. <u>160</u>							
TYPE OF SCREEN OR PERFORATION MATERIAL:				① PVC	10 Asbestos-Cement		
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 Other (Specify)			
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:				5 Guazed wrapped	① Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes				
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	ft.			
SCREEN-PERFORATED INTERVALS:				From <u>8.2</u> ft. to <u>9.2</u> ft., From ft. to ft.			
				From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:				From <u>2.3</u> ft. to <u>9.3</u> ft., From ft. to ft.			
				From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other.....
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? S How many feet? 23

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-30-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 447 This Water Well Record was completed on (mo/day/yr) 6-7-03 under the business name of Miller Drilling by (signature) E. Miller