V	VATER WELL RE	CORD Form WWC-5	KSA 82a-12	212 ID No.				
1 LOCATION OF WATER WELL: County: Harvey	Fraction	Azz	Secti	on Number	Township Nun	ıber	Range Nu	umber
County: Harvey Distance and direction from nearest t	town or city street	NW 14 5W 14	<u> 2</u>	7	T 24	S	R 4	E/W
Justinee and direction north hearest t	own or city street	2 5 of Ha	ithin city?	_				
2 WATER WELL OWNER:	endall	Kurlan	1) / Eac	<u>a </u>				
RR#, St. Address, Box # : /3	122 5cm	844 ST			Board of Agric	sultura Div	ision of Water	Посолительн
City, State, ZIP Code : Ha	ilstead,	KS 67056			Application No		ision of water	Hesources
3 LOCATE WELL'S LOCATION WITH	H 4 DEPTH OF	COMPLETED WELL	3.2	ft. ELEVATI	ON:			
AN "X" IN SECTION BOX:	Depth(s) Grou	ndwater Encountered 1 IC WATER LEVEL 36 Imp test data: Well water		ft. 2	2	ft. 3		ft.
I I	WELL'S STAT	IC WATER LEVEL 3.6	ft. below	/ land surface	measured on mo/d	ay/yr	7-23-	03
	Est. Yield	mp test data: Well water	was	H. aft	ter	hours pur	nping	gpm
NW NE	WELL WATER	TO BE USED AS: 5 Pu	ıblic water su	pply {	B Air conditioning	11 Inie	ction well	gpm
W	2 Irrigation		I field water s	supply 9	9 Dewatering	12 Oth	er (Specify bel	low)
w ×	2 iiiigalioi	4 Industrial 7 Do	mestic (lawn	& garden) 10	0 Monitoring well			
swse	Mas a shamin							
	mitted	al/bacteriological sample su	bmitted to De	partment? Ye Wat	s; er Well Disinfected?	If yes, mo/		le was sub- lo
				vva.	er wen bisiniected:	(GS)	IN	10
TYPE OF BLANK CASING USED).	5 Wrought iron	9 Conorate		040140 10141		L -	
		6 Asbestos-Cement	8 Concrete tile 9 Other (specify below)		CASING JOIN	CASING JOINTS: Glued Clamped		
②PVC 4 ABS		7 Fiberglass				Throad	ad	
Blank casing diameter5	in. to			.in. to	ft., Dia		in. to	ft.
Casing height above land surface	<i>l.</i>	in., weight	2. <i>9</i>	lb	s./ft. Wall thickness	or guage i	No. 160	
TYPE OF SCREEN OR PERFORATI 1 Steel 3 Stainle		5 Fiberglass	₽ PVC			tos-Cemen		
	nized Steel	6 Concrete tile	9 ABS	(SR)		(Specify) used (open	hole)	•••••
SCREEN OR PERFORATION OPEN	INGS ARE:	5 Guazeo	wrapped		8 Saw cut		•	b 1 3
	Mill slot	6 Wire w		C	9 Drilled holes	ſ	1 None (open	noie)
2 Louvered shutter 4	Key punched	7 Torch c			10 Other (specify) .			
SCREEN-PERFORATED INTERVAL	S: From	122 ft. to!	32	ft., From	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ft. to		ft
GRAVEL PACK INTERVAL	From	2.3ft. to	7	ft., From		ft. to	•••••	ft.
GHAVEL PACK INTERVAL	5. From	π. to 5 f to	40	ft., From	••••••	ft. to		ft.
GROUT MATERIAL: 1 Ne	at cement	2 Cement grout 3 ft., From 6.4	Bentor	nite 4 (Other		***************************************	
Grout Intervals: From	It. to	الم الماسية ال	ft. to .					
		7 Dit		10 Livestoc	•		ndoned water	well
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool		7 Pit privy Ø Sewage lag		11 Fuel storage12 Fertilizer storage		15 Oil well/Gas well		
3 Watertight sewer lines 6 See		9 Feedyard	joon	12 Fertilize 13 Insectici		16 Othe	er (specify belo	ow)
Direction from well?	spage bit	5 i ccayara			feet? /50			••••••
FROM TO	LITHOLOGIC	LOG	FROM	TO		SING INTE	BVALS	
0 20 Gr	Clay				1 2000	ZING INTE	NVALO	
20 63 F-M	Sand							
63 70 Gr C.	lac						- 100	
	ud							
	Sand					184	,	
131 140 Sandy	Or Clay							
-								
			_					
					194			
CONTRACTOR'S OR LANDOWALL	EB'S CEDTIFICA	IION, Thist "	(n - ·				er	
CONTRACTOR'S OR LANDOWNED Completed on (mo/day/year)								
/ater Well Contractor's Licence No	447	This Water We	ell Record wa	and this recor is completed a	u is true to the best on (mo/day/yr)	my knowl	eage and belie	∍r. Kansas
nder the business name of	riller D	rilling		by (sia	nature) Fin	- 100-	· 	
NATE OF THE PARTY					· Cpn	KKE	·	