


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SE 1/4 SW 1/4 NW 1/4	1	T 24 S	R 2 E (W)
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: LEGG Company					
RR#, St. Address, Box #: 325 E. 10th Street					
City, State, ZIP Code: Halstead, KS 67056					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 23 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes N/A No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 2 in. to 28 ft., Dia		7 Fiberglass		Threaded	
Casing height above land surface 36 in., weight		lbs./ft. Wall thickness or gauge No. SCH 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC		8 RMP (SR)		10 Asbestos-Cement	
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS				11 Other (Specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 28 ft. to 38 ft.					
GRAVEL PACK INTERVALS: From 21 ft. to 38 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 21 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	CLAY, BLACK, TRACE PLASTERITY			
8	19	CLAY, SOME SILT, BROWN, TRACE PLASTERITY			
19	24	CLAY, BROWN, TRACE PLASTERITY			
24	38	SAND, DARK GRAY, POORLY SORTED			
38	40	CLAY, DARK GRAY, TRACE PLASTERITY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 759 This Water Well Record was completed on (mo/day/yr) 9-27-05 under the business name of RAZEK Environmental, LLC by (signature) [Signature]					