

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>		<u>NE 1/4 NE 1/4 NW 1/4</u>	<u>2</u>	T <u>24</u> S	R <u>2</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>520 West 6th, Halstead, Ks.</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>520 W. 6th</u> <u>Halstead, Ks.</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>28'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>18'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>18.23</u> ft. below land surface measured on mo/day/yr <u>8-27-98</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2</u> in. to <u>28</u> in. to in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No. <u>X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes.....No. <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued.....Clamped.....					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded.....					
7 Fiberglass Threaded..... <u>X</u>					
Blank casing diameter <u>2 3/8</u> in. to <u>10 1/2</u> ft. Dia. in. to ft. Dia. in. to <u>SDR 13</u> ft.					
Casing height above land surface <u>Flush</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
10 Other (specify)					
SCREEN-PERFORATED INTERVALS:					
From <u>27 1/2</u> ft. to <u>10 1/2</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS:					
From <u>28</u> ft. to <u>9</u> ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>9'</u> ft. to <u>4'</u> ft. From <u>4'</u> ft. to <u>0'</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <u>Fourer</u> 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? <u>In oil field</u> How many feet? <u>0</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Brn-blk silty clay, no odor, firm, moist to dry.			
7	17	Qtz pebble, pea gravel fill, dry, loose, no odor.			
17	21	gray blk silty clay, moist, highly plastic, no odor.			
21	28	Lt gray silty sand to sand, fine-coarse, wet, no odor.			
Fl. mt OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-26-98</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>9-14-98</u>					
under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					