


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Township Number		Range Number	
County: Harvey		NE 1/4 NE 1/4 NW 1/4		2		T 24 S R 2 EW	
Distance and direction from nearest town or city street address of well if located within city? 520 West 6th, Halstead, Ks.							
2 WATER WELL OWNER:		USD #440/Halstead High School					
RR#, St. Address, Box #		520 W. 6th					
City, State, ZIP Code		Halstead, Ks.					
Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25' ft. ELEVATION:					
		Depth(s) Groundwater Encountered: 19.84 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL: 19.84 ft. below land surface measured on mo/day/yr 8-27-98					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter: 8 1/2" in. to 25" ft., and in. to ft.					
		WELL WATER TO BE USED AS:					
		5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)		Welded					
2 PVC 4 ABS		Threaded X					
Blank casing diameter: 2.375 in. to 10" ft., Dia in. to SDR 13 ft.							
Casing height above land surface: Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 25' ft. to 10' ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 25' ft. to 8' ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 8' to 3' ft., From 3' to 0' ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? North		How many feet? 80'					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 16 Grass-brn gray hard clay, dry, no odor.							
16 20 Moist to wet, soft, lt brn clayey silt, no odor.							
20 25 Lt brn gray fine-coarse sand, wet, poorly sorted, no odor.							
		Fl. mt OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-26-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 9-14-98 under the business name of JB Environmental Drilling by (signature) James Becker							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							