

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		SE 1/4 NE 1/4 NE 1/4	29	T 24 S	R 2 E/W
Distance and direction from nearest town or city street address of well if located within city? 4 miles south & 3 miles West of Halstead					
2 WATER WELL OWNER: Jerry Morris RR#, St. Address, Box # : RR 2 City, State, ZIP Code : Sedgwick, KS 67135 Board of Agriculture, Division of Water Resources Application Number: N/A					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 41 ft. below land surface measured on mo/day/yr ... 7/17/98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 50-100 gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 8 in. to 86 ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	12 Other (Specify below) Stockwell
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
X PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 65 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		X Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 65 ft. to 85 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 85 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	X Bentonite	4 Other	
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	2	Topsoil			
2	18	Brown Sandy Clay			
18	24	Fine to Medium Sand Tan			
24	36	Brown Sandy Clay			
36	44	Medium to Coarse Sand, Gray			
44	48	Brown Sandy Clay			
48	85	Medium to Coarse Gray Sand			
85	86	Green Sandy Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/17/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 8/4/98 under the business name of Peterson Irrigation, Inc. by (signature) <i>Mike Peterson</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					