

LOCATION OF WATER WELL: HARVEY	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 18	Township Number 24 SOUTH	Range Number 02WEST
-----------------------------------	----------------------------------	----------------------	-----------------------------	------------------------

Distance and direction from nearest town or city street address of well if located within city?
From Halstead, KS: 3 miles south and 3 miles west, located 28 feet west of SW corner of house at 7125 S. Golden Prairie Rd, Halstead

WATER WELL OWNER: ROBERT SITTS

RR#, St. Address, Box #: 7125 S. GOLDEN PRAIRIE ROAD
City, State, ZIP Code: HALSTEAD KS 67056

Board of Agriculture, Division of Water Resources
Application Number: NA

MARK WELL'S LOCATION WITH AN "X" IN SECTION BOX

N

	X

S

DEPTH OF WELL 35 ft.

WELL'S STATIC WATER LEVEL 15.0 ft.

WELL WAS USED AS:

1 <u>Domestic</u>	5 Public Water Supply	9 Dewatering
2 Irrigation	6 Oil Field Water Supply	10 Monitoring Well
3 Feedlot	7 Lawn and Garden Only	11 Injection Well
4 Industrial	8 Air Conditioning	12 Other

Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒

If yes, mo/day/yr sample was submitted : / /

WaterWell Disinfected: Yes ☒ No ☐

TYPE OF BLANK CASING USED:

1 <u>Steel</u>	3 RMP (SR)	5 Wrought	7 Fiberglass	9 Other ____
2 PVC	4 ABS	6 Asbestos-Cement	8 Concrete Tile	

Blank casing diameter 2.0 in. Was casing pulled? Yes ☐ No ☒ if yes, how much 0.0 ft bls
Casing height above or below land surface 8.5 feet.

GROUT PLUG MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Plug Intervals: From 35 ft. to 7.5 ft.

What is the nearest source of possible contamination:

1 Septic tank	6 Seepage pit	11 <u>Fuel Storage</u>	16 Other -
2 Sewer lines	7 Pit privy	12 Fertilizer storage	
3 Watertight sewer lines	8 Sewage lagoon	13 Insecticide storage	
4 Lateral lines	9 Feedyard	14 Abandoned water well	
5 Cess Pool	10 Livestock pens	15 Oil well / Gas well	

Direction from well? south How many feet? 15

FROM	TO	PLUGGING MATERIALS
35.0	7.5	Bentonite, HolePlug
7.5	7	Concrete

Plugging witnessed by Tim Boese, Equus Beds GMD2.
Well is located in 7 foot deep pit. Casing was cut off 1.5 feet below pit concrete floor. Bentonite grout (Holeplug 3/8 chips) was used to plug well from bottom to top. Grout extended over top of casing to 0.5 feet below pit floor. Concrete was then poured over top of bentonite grout to pit floor level.

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was plugged under my jurisdiction and was completed on (mo/day/year) 04 / 27 / 2006 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. NA under the business name of NA
by (signature) Robert Sitts Date: 5-9-06

INSTRUCTIONS: Use typewriter or ball point pen. Please press firmly and print clearly. Please fill in blanks, and underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 785/296-3565. Send one to Water Well Owner and retain one for your records.