

Range Number

R 2 □E

Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m

Water well disinfected? ☐ Yes ☒ No

From..... ft. to ft., From ft. to ft.

Direction from well Distance from well ...Over 1000 feet

Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy

Sargent Drilling
INDUSTRIAL ENGINEERING
COMPLETE MUNICIPAL AND INDUSTRIAL
WELL AND PUMP SERVICE

PO Box 367
Geneva, NE 68361-0367

846 South 13th St.

Phone: (402) 759-3902
1-888-496-3902

TEST HOLE LOG

CUSTOMER: City of Wichita	
WELL ID: MW3S	
LOCATION: SW ¼ SW ¼ SE ¼ SE ¼, 17-T24S-R2W, Harvey Co., KS	
LATITUDE: 37° 57' 21.9"	
LONGITUDE: 097° 33' 36.2"	
FOOTAGES: 57' from the South section line and 1336 feet from the East section line.	
DATE: 11-11-09	DRILLED BY: CL

SWL:
PWL:

<u>from feet</u>	<u>- to feet</u>	
0	6	Clay
6	20	Fine, medium and coarse sand
20	47	Fine, medium and coarse sand and fine and medium gravel

Well Depth: 45'
Bore Hole Dia: 6"

Plain casing: 35' of 2"
Perf casing: 10' of 2" slot size: .20"

Gravel pack from 30' to 45'
Bentonite from 0' to 30'

dh