WATER WELL REC	CORD OB48	s Form	WWC-5	Division of Wate	er Resources App. No).	
1 LOCATION OF WA		Fraction		Section Number	Township No.	Range Number	
County: Harvey		NE 1/4 NE 1/4 1			T 24 S	R 2 □E ✓W	
Street/Rural Address of	of Well Location;	if unknown, distanc	e & direction	Global Positioning	g System (GPS) in	formation:	
1			= :	Landide:vsv		(in decimal degrees)	
1/2 mile north of intersection SW 96th St and 167th St. W. on the west side of 167th St.				Elevation: 32 \\ \RZ, \\			
				- <u>Datum</u> : ☐ WGS 8	<u>Datum</u> : WGS 84, K NAD 83, NAD 27 \ 7/10/2012)		
2 WATER WELL OWNER: City of Wichita RR#, Street Address, Box #: 455 North Main St.				GPS unit (Make/Model: Garmin			
City, State, ZIP Code : Wichita, KS 67202			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
TO LOCATE WELL	-			Est. Accuracy:	3 m, ☐ 3-5 m, ☐	5-15 m, >15 m	
3 LOCATE WELL WITH AN "X" IN	4 DEPTH OF	COMPLETED WE	ELL 37	ft.			
SECTION BOX:	Depth(s) Ground	dwater Encountered	(1).17.3	ft. (2)	ft. (1	3) ft.	
N							
			Global Positioning System (GPS) information: Latitude: 37°, 56°, 01, 32" (in decimal degrees) Latitude: 37°, 56°, 01, 33°,				
w NW NE E	Bore Hole Diam	eter 6 in. to	37	ft., andin	. to	ft.	
~ 	WELL WATER	TO BE USED AS:	☐ Public wa	er supply 🔲 Ge	cothermal	njection well	
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Monitoring well Dewatering Other (Specify below)							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
mile Water well disinfected? ☐ Yes ☑ No							
CASING JOINTS: XXXIXX							
Casing diameter .4							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel							
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATE	SCREEN-PERFORATED INTERVALS: From						
GRAVEL PACK INTERVALS: From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout 7 Bentonite Cother							
Grout Intervals: From							
Septic tank							
Direction from well						••••••	
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
Log atta	ached						
						7.11.11.11	
							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, □ reconstructed, or □ plugged							
under my jurisdiction and was completed on (mo/day/year) .1.1/09/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No7.55 This Water Well Record was completed on							
under the business name of Sargent Drilling by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment. Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212				Check: UW	nite Copy, 🔲 Blu	e Copy, 🔲 Pink Cop	

Sargent Drilling

INDUSTRIAL ENGINEERING COMPLETE MUNICIPAL AND INDUSTRIAL WELL AND PUMP SERVICE

PO Box 367 Geneva, NE 68361-0367 846 South 13th St.

Phone: (402) 759-3902

1-888-496-3902

TEST HOLE LOG

CUSTOMER: City of Wichita

WELL ID: OB48S

LOCATION: NE ½ NE ½ SE ½, 28-T24S-R2W, Harvey Co., KS

LATITUDE: 37° 56' 01.3"

LONGITUDE: 097° 32' 16.0"

FOOTAGES: 2513 feet from the South section line and 190 feet from the East section line.

DATE: 11-9-09 DRILLED BY: CL

SWL: PWL:

from feet
0-to feet
16Topsoil and clay1620Fine, medium and coarse sand2037Fine, medium and coarse sand and fine gravel

Well Depth: 37' Bore Hole Dia: 6"

Plain casing: 27' of 2"

Perf. casing: 10' of 2"

slot size: .020"

Gravel pack from 22' to 37' Bentonite from 0' to 22'