CORRECTED WATER WELL RECORD OB10S Form	a WWC-5	Division of Water	r Resources App. No	,
1 LOCATION OF WATER WELL: Fraction				Range Number
County: Harvey NE 1/4 NE 1/4	NE 14 NW 14	8		R 2 □E ☑W
Street/Rural Address of Well Location; if unknown, dista		Global Positioning		
from nearest town or intersection: If at owner's address,	Latitude: 37* 59' 4.3" (in decimal degrees)			
		Latitude: .37* 59' 4.3" (in decimal degrees) Longitude: .097* 33' 55.8" (in decimal degrees)		
1/2 mile east of intersection SW 48th St. and 199th St. on the south		Elevation:		
side of SW 48th St.		Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: City of Wichita		Collection Method:		
RR#, Street Address, Box #: 455 North Main Street		GPS unit (Make/Model.Garmin)		
City, State, ZIP Code : Wichita, KS 67202	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
VICINIE, NO 07202	Est. Accuracy:			
3 LOCATE WELL	45			
WITH AN "X" IN 4 DEPTH OF COMPLETED V	WELL .45	ft.		
SECTION BOX: Depth(s) Groundwater Encounter	ed (1).28	ft. (2)	ft. (3	3) ft.
N WELL'S STATIC WATER LEV	EL28ft.	below land surface r	neasured on mo/da	ay/yr10/22/09
Pump test data: Well	water was	ft. after	hours pump	oing gpm
EST. YIELDgpm. Well	water was	ft. after	hours pump	oing gpm
w				ft.
WELL WATER TO BE USED A	S: Public water	er supply 🔲 Ge	othermal 🔲 Ir	njection well
		r supply De		Other (Specify below)
□ Irrigation □ Industrial	☐ Domestic-lav	n & garden Mo	nitoring well Ob	servation
Was a chemical/bacteriological sa				
s If yes, mo/day/yr sample wa				
Water well disinfected? ☐ Yes				
			••••	
CASING JOINTS: KENERAL Clamped Welder	ed KI Inreaded			
Casing diameter .2 in. to .35 ft., Diamet	ter in. 1	o tt., D	ameter	in. to ft.
Casing height above land surface24 in., W	eight(U.S	lbs./ft., Wall thic	kness or gauge No)154
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel ☑ PVC		Other (Specify)		•••••
Brass Galvanized Steel None used (o	pen hole)			
SCREEN OR PERFORATION OPENINGS ARE:				
☐ Continuous slot				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
From				
GRAVEL PACK INTERVALS: From30 ft. to45 ft., From ft. to ft.				
From				
6 GROUT MATERIAL: Neat cement Cement	grout Z Benton	ite		
Grout Intervals: From .0 ft. to .30 ft.,	From	t. to It.,	From	ft. toft.
What is the nearest source of possible contamination:				
Septic tank	Livestock p			er (specify below)
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well				
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard	☐ Fertilizer st			
Direction from well		rom well Over 10		CODIO BIZZDELLI
FROM TO LITHOLOGIC LOG	FROM	TO LITHO. LO	Cont.) or PLU	GGING INTERVALS
Log attached				
:				
T CONTRACTORS OF LANDOWNERS CERTIFICA	TION: This wat-	r well was [7]	atod 🗀 manarat	oted on Claiman
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) .10/22/2009 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No755. This Water Well Record was completed on (plo/defrear) 11/06/2009				
under the business name of Sargent Drilling by (signature) by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212		Check: Wh	ite Copy, Blu	e Copy, Pink Copy

Sargent Drilling

INDUSTRIAL ENGINEERING COMPLETE MUNICIPAL AND INDUSTRIAL WELL AND PUMP SERVICE

PO Box 367 Geneva, NE 68361-0367 846 South 13th St.

Phone: (402) 759-3902

1-888-496-3902

TEST HOLE LOG

CUSTOMER: City of Wichita

WELL ID: OB10S

LOCATION: NE ¼ NE ¼ NW ¼, 8-T24S-R2W, Harvey Co., KS

LATITUDE: 37° 59' 04.3"

LONGITUDE: 097° 33' 55.8"

FOOTAGES: 4347 feet from the South section line and 2923 feet from the East section line.

DATE: 10-22-09

DRILLED BY: CL

SWL: PWL:

from feet -	to feet	
0	15	Topsoil and clay
15	20	Fine, medium and coarse sand
20	46	Fine, medium and coarse sand and fine gravel

Well Depth: 45' Bore Hole Dia: 6"

Plain casing: 35' of 2"

Perf. casing: 10' of 2"

slot size: .020"

Gravel pack form 30' to 45' Bentonite from 0' to 30'