

Form WWC-5

--

1 LOCATION OF WATER WELL: County: Harvey		Fraction NE 1/4 NE 1/4 NE 1/4 SE 1/4	Section Number 16	Township No. T 24 S	Range Number R 2 E W																																																																		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here ☐ 1/2 mile north of intersection 167th St. W. and SW 72nd St. on the west side of 167th St.			Global Positioning System (GPS) information: Latitude: 37° 57' 46.2" (in decimal degrees) Longitude: 097° 32' 16.4" (in decimal degrees) Elevation: _____ Datum: ☐ WGS 84, ☒ NAD 83, ☐ NAD 27 Collection Method: ☐ GPS unit (Make/Model: Garmin) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m																																																																				
2 WATER WELL OWNER: City of Wichita RR#, Street Address, Box #: 455 North Main St. City, State, ZIP Code : Wichita, KS 67202																																																																							
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N W E S [Diagram of a 36-section grid with an 'X' in the SE section] [Scale bar: 1 mile]		4 DEPTH OF COMPLETED WELL 45 ft. Depth(s) Groundwater Encountered (1) 17.11 ft. (2) _____ ft. (3) _____ ft. WELL'S STATIC WATER LEVEL 17.11 ft. below land surface measured on mo/day/yr. 10/21/09 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm EST. YIELD _____ gpm. Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter .6 in. to .50 in. and _____ in. to _____ in. WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☒ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well ☐ Observation Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No If yes, mo/day/yr sample was submitted _____ Water well disinfected? ☐ Yes ☒ No																																																																					
5 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other _____ CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☒ Threaded Casing diameter .2 in. to .35 ft., Diameter _____ in. to _____ ft., Diameter _____ in. to _____ ft. Casing height above land surface .24 in., Weight .703 lbs./ft., Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☒ PVC ☐ Other (Specify) _____ ☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous slot ☒ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) _____ SCREEN-PERFORATED INTERVALS: From .35 ft. to .45 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From .30 ft. to .45 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft.																																																																							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other _____ Grout Intervals: From 0 ft. to .30 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: ☒ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well _____ Distance from well Over 1000 feet <table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>LITHO. LOG (cont.) or PLUGGING INTERVALS</th></tr></thead><tbody><tr><td></td><td></td><td>Log attached</td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS			Log attached																																																									
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS																																																																		
		Log attached																																																																					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 10/21/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 755 This Water Well Record was completed on (mo/day/year) 12/02/2009 under the business name of Sargent Drilling by (signature) [Signature] INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html .																																																																							

Sargent Irrigation

WELL AND PUMP SERVICE

PO Box 268
Holdrege, NE 68949

825 Brewster Road

Phone: (308) 995-6143
1-800-860-2946

TEST HOLE LOG

CUSTOMER: Wichita, KS	
WELL ID: OB18S	
LOCATION: NE ¼ NE ¼ NE ¼ SE ¼, 16-T24S-R2W, Harvey Co., KS	
LATITUDE: 37° 57' 46.2"	
LONGITUDE: -97° 32' 16.4"	
FOOTAGES: 2524' from the South section line and 197 feet from the East section line.	
DATE: 10/21/09	DRILLED BY: Kyle Schoff, Doug Rezac, Cody Hanson

SWL:

PWL:

GPM:

from feet - to feet

0	5	Heavy clay with traces of sandy
5	10	Sandy clay with fine to medium gravel
10	15	Sandy clay with fine to medium gravel
15	20	Fine to medium gravel with sandy clay
20	40	Fine to medium gravel with thin sandy clay streaks
40	45	Coarse sand to fine and medium gravel
45	50	Fine to medium gravel with gray shale

Well Information:

Well depth: 45
Plain casing: 35'
Perf. Set: 35-45'

Bore hole: 6"
Perf. casing: 10'
Gravel: 30-45'

Casing size: 2"
Slot size: .020"
Grout: 0-30'