WATER WELL RECORD		Form WWC-5		D	Division of Water Resources App. No.				
1 LOCATION OF WATER WELL:		Fraction		Secti	Section Number Township No.				
		1/4 SW 1/4 SW 1/4 SW 1/4				T 24 S			
	if unknown, distance & direction				g System (GPS) in				
from nearest town or intersection: If at owner's address, check here			k here 🔲.		Latitude: (in decimal degrees)				
13/08 Sw 60th			Eleva	Longitude: (in decimal degrees) Elevation:					
2 WATER WELL OWNER: Am see leid					Datum: WGS 84, NAD 83, NAD 27 Collection Method:				
2 WATER WELL OWNER: RR#, Street Address, Box #: City State 7IB Code 725 Main				GPS unit (Make/Model:)					
City, State, ZIP Code : Halstead, K.			17056	=	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
	Hai	stead, K)	6 /05 0	Est. A	Accuracy: <a> </a>	3 m, □ 3-5 m, □	5-15 m, [	]>15 m	
3 LOCATE WELL	4 DEDTH OF	COMDI ETEN WEI	T 18.5	-	<b>A</b>				
WITH AN "X" IN SECTION ROX:	WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 185 ft. (2) ft. (3)							ft	
N	WELL'S STATIC WATER LEVEL. 36ft. below land surface measured on mo/day/yr.56								
Pump test data: Well water was								gpm	
					ft. after hours pumping gpm				
W Bore Hole Diameter 8									
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well									
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
Irrigation   Industrial   Domestic-lawn & garden   Monitoring well									
was a chemical/bacteriological sample submitted to Department? \(\sigma\) Yes \(\kappa\) No									
S If yes, mo/day/yr sample was submitted									
water went distincted: El 163   140									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Marginet Clamped Welded Threaded									
Casing diameter 5 in. to 18.5 ft., Diameter in. to ft., Diameter in. to ft.									
Casing height above land surface									
Steel Stainless Steel VPC Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS:         From									
GRAVEL PACK INTERVALS: From 2.3 ft. to 1.40 ft., From ft. to ft.									
From 145 ft to 19/ ft From ft to ft									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
	ft. to	ft., Fron	n 140	. ft. to	1.45 ft.,	From	. ft. to	ft.	
What is the nearest source									
Septic tank		☐ Livestock ☐ Fuel stora		Insecticide		er (specify	below)		
Sewer lines Cesspool			ige storogo						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer Direction from well						's mot it			
FROM TO	LITHOLOG		FROM	TO		OG (cont.) or PLU			
	Clay	10 200	188	191	Shale		OOII1O I	ITTLKTALS	
14 43 F-C		a 19	7.5.5		Juli				
43 70 F-C									
70 76 Clas		,							
		layers Clare							
106 137 F-C	Sand - To								
137 138 WT 1	Rock								
138 158 51174	Clay-Br					<u> </u>			
158 175 F-c Sand-Tan									
175 188 layers Censented Sand + Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year)									
Kansas Water Well Contractor's License No									
INSTRUCTIONS: Use typewi								Cond there is	
(white, blue, pink) to Kansas D	Department of Health	and Environment, Bureau	of Water, Geo	logy Section	on, 1000 SW Jac	ckson St., Suite 420,	Topeka, Kar	nsas 66612-1367.	
Telephone 785-296-5522. Sen	d one copy to WAT	ER WELL OWNER and	retain one for	your recor	rds. Include fee	of \$5.00 for each co	onstructed v	vell. Visit us at	
http://www.kdheks.gov/waterwe	ll/index.html.								
KSA 82a-1212									