	WATER W	ELL RF	CORD	For	m WW	C-5 KS	SA 82a-1212			111050
1 LOCATION OF WATER WELL:	FRACTION					ON NUMBER			RANGE N	
Harvey	SW 1/4		1/4	NE 1	1/4	2	T 24	S	R 2V	- E/VV
Distance and direction from nearest town or	city street address of we	ell if located w	rithin city?							
1430 S. Main	Halstead, Kans	sas	DITO	YOM!						
	LAUSMEYER	CONST	RUCT	ION				Board of Agr	iculture, Division of N	Water Resource
111111111111111111111111111111111111111	0008 W. York				710	CODE: 6	7215	Application Nu	mber:	
CITY, STATE: W	Vichita, Kansas			116		CODE	ELEVATION:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COM			110	ft.		CLLVIII	ft.		ft.
N	Depth of groundwar			31		ALL AND CI	JRFACE MEASU		day/yr: 8/1	9/20
	WELL'S STATIC V			Nell water		M THIND SO	ft. after		s of pumping @	gpm
	Est. Yield:	ump test da gpm		Well wate			ft. after		s of pumping @	gpm
W W	Bore Hole Diamet			· · · · · · · · · · · · · · · · · · ·		16 ft	. and	in.	to	ft.
= "	WELL WATER TO		AS:					9. Dewater	mg -	ection well
sw se	1. Domestic	3. Feedlot	5. Pu	blic wate	r supply		and garden only			Specify below
		4. Industria			ter supply		nditioning	10. Monitor	what mo/day/yr	was sample
S	Was a chemical/bac submitted	cteriological s	ample subn	nitted to De	partment?	Y ES Was '	NO Water Well Disinf		YES	NO
5 TYPE OF CASING USED:	<u> </u>				9 01	her (Specif		ING JOINTS:	Glued	Threaded
(~ l	M (SR) 5. Wroug	nt Iron	7. Fib	erglass		R-26	, 20.077		Welded	Clamped
2. PVC 4. ABS	S 6. Asbes	tos-Cement	8. Co	ncrete tile	, אוטפ	X-20				
Blank casing diameter 5	in. to	96 ft	i., I	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface:	12 in.,		Weig	ght: 2	2.35 H	os. / ft.	Wall th	ickness or gau	ige No21	4
TYPE OF SCREEN OR PERFORA	TION MATERIAL:			_						
Steel 3. Stainless Ste	eel 5. Fibergla	ss (7. PV		9. A			her (specify)		
2. Brass 4. Galvanized	6. Concrete	e Tile	8. RM	P (SR)	10. A	sbestos-Ce	ement 12. No	one used (oper	n hole)	
SCREEN OR PERFORATION OPE	NINGS ARE:								44 11	anan hala)
1. Continuous slot 3. M	lill slot	5. Gauzed v	vrapped		7. To	rch cut	9. Drill	ed holes	11. None (open hole)
2. Louvered shutter 4. K	ey punched	6. Wire wra	pped		8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERV	VAL From	96	ft.	to	116	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVAL	LS: From	24	ft.	to	116	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1.1	Neat cement	2 Ce	ment Gro	out		B. Bentonite	e	Other ben	tonite hole p	lug
Grout Intervals: From	-	0	ft.,	From	ft.	to	ft.,	From	-	24 ft.
What is the nearest source of possit		7 Dit priv	v	10	Livestoc	k nens	13 Insect	icida storana	15. Oil well	/Gas well
1. Septic tank 4. Lateral lines								specify below)		
	ess Pool	8. Sewage	_			•	14. Aband	on water wel	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, ,
3. Watertight sewer line 6. So Direction from well? East	eepage pit	9. Feed ya	ira	12	2. Fertilize	storage	How m	any feet? 10	ft plus	
From To	LITHOLOG	IC LOG			From	To	110W111		OGIC LOG	
0 3 topsoil	LITTIOLOC	NO LOO			1.0111	, · · ·	 	LITTIOL	00.0 200	
3 31 clay										
31 45 fine sand										
45 110 clay							ļ			
110 116 medium s	and					 	 			
						 	 			
										
 							 			
7 Contractor's or Landowner's C	ertification: This water	er well was	1. Cons	tructed) 2. red	onstructed	d or 3.	olugged	under my jurisdio	ction and
was completed on (mo/day/year)	8/19/202						knowledge and b		.,	
Kansas Water Well Contractor's Li							on (mo/day/year		21/20	
				·ato Well			. ,			
under the business name of Ha	rp well and Pu	mp Serv	ice		by (sig	nature)	To	rad S	. Hart)