sent 11/6/75

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

T R EW sec 1/4 1/4 1/4 No.

WATER WELL RECORD
KSA 82a-1201-1215
DBB
NW NW SE

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	HODGMAN			19	24 S	21W

Distance and direction from nearest town or city: 4.5N, 1.5 W, .5N of Belfont East

Street address of well location if in city:

3 Owner of well: LOYD COLE

Address: JETMORE KANSAS

Locate with "X" in section below:

Sketch map:

N, W, E, S, 1 Mile

BELFONT EAST

2 Type and color of material	From	To
TOPSOIL	0	3
CLAY	3	80
SAND	80	100
CLAY	100	115
DAKATA SAND	115	175
SHALE	175	
8 P 0 0' RR		
CRETACEOUS WELL		

(use a second sheet if needed)

4 Well depth: 175 ft. Date of completion 8-2-75
Well diameter 28 in.

5 ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary

6 Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐

7 Casing: Material STEEL Height: above/below Surface 12 in.
Threaded ☐ Welded ☒ Weight 37 lbs./ft.
Diam. 16 in. to 175 ft. depth Drive shoe? ☐ Yes ☒ No
in. to ft. depth

8 Screen:
Manufacturer DOERR
Type PUNCH Dia. 16"
Slot gauze 3/16 Length 60
Set between 115 ft. and 175 ft.
Fittings:
Gravel pack ☒ Yes ☐ No Size range of material 1/4 X 58

9 Static water level: 115 ft. below land surface Date 8-2-75

10 Pumping level below land surfaces: 170 ft. after 2 hrs. pumping 400 g.p.m.
ft. after hrs. pumping g.p.m.
Estimated maximum yield 400 g.p.m.

11 Water sample submitted: ☐ Yes ☒ No Date

12 Well head completion: ☐ Pitless adapter ☐ Inches above grade

13 Well grouted? ☒ Yes ☐ No
☐ Neat cement ☐ Bentonite ☐ Clay MIX
Depth: From 10 ft. to 0 ft. GROUND LEVEL

14 Nearest source of possible contamination: NONE
ft. Direction Type
Well disinfected upon completion? ☐ Yes ☒ No

15 Pump: GOULDS ☐ Not installed
Manufacturer's name
Model number HP 80 Volts GEAR DRIVE
Length of drop pipe 160 ft. capacity 400 g.m.p.
Type:
☐ Submersible ☒ Turbine
☐ Jet ☐ Reciprocating
☐ Certrifugal ☐ Other

16 Remarks: elevation

FLAT 350 Gallon Sand Rock Formation
TOP 2348
100
2248

Topography:
☐ Hill
☐ Slope
☐ Upland
☐ Valley

17 Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Business name BRAUD DRILLING CO. License No. 217
Address BOX 56 BUCKLIN
Signed Authorized representative Date 8-24-75

24 21W 19 NW NW SE

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5

677-H