

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction C $\frac{1}{4}$ SE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 6	Township Number T 24 S	Range Number R 29 E/W
---------------------------	---	---------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

8 1/8 north 1 east of Charleston

2 WATER WELL OWNER:	J. Miller	Mustang Drilling	
RR#, St. Address, Box # :	Garden City, Ks.	Box 1609	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :		Great Bend, Ks. 67530	Application Number: T84-39

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 17.5 ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1 47 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 101 ft. below land surface measured on mo/day/yr 1-19-84

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield NA gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 17.5 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes HTH No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded

Blank casing diameter 5 in. to 13.5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 2.58

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)
2 Brass	4 Galvanized steel	9 ABS

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 13.5 ft. to 17.5 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 17.5 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	-------------------

Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)

13 Insecticide storage

Direction from well?

west How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
------	----	----------------	------	----	----------------

0 2 Top soil

2 21 ~~0~~ Clay21 46 ~~0~~ Sand and sandy clay46 47 ~~28~~ Rock

47 101 Sand and gravel & clay layers

101 145 Sand and gravel

145 158 ~~17~~ Sand and gravel & rock layers158 175 ~~19~~ Shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-19-84 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 2-1-84

under the business name of Rosencrantz-Bemis Ent. by (signature) *Lora Dodson*

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

1 LOCATION OF WATER WELL:	Fraction C $\frac{1}{4}$ SE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 6	Township Number T 24 S	Range Number R 29 E/W	
Distance and direction from nearest town or city street address of well if located within city?					
8 1/8 north 1 east of Charleston					
2 WATER WELL OWNER:	J. Miller	Mustang Drilling			
RR#, St. Address, Box # :	Garden City, Ks.	Box 1609	Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :		Great Bend, Ks. 67530	Application Number: T84-39		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 17.5 ft. ELEVATION:				
Depth(s) Groundwater Encountered 1 47 ft. 2 ft. 3 ft.					
WELL'S STATIC WATER LEVEL 101 ft. below land surface measured on mo/day/yr 1-19-84					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield NA gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter 10 in. to 17.5 ft. and in. to ft.					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes HTH No					
5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped		
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded		
2 PVC	4 ABS	7 PVC	Threaded		
Blank casing diameter 5 in. to 13.5 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 2.58					
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement			
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)		
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
1 Continuous slot	6 Wire wrapped	9 Drilled holes			
2 Louvered shutter	7 Torch cut	10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 13.5 ft. to 17.5 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 17.5 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
13 Insecticide storage					
Direction from well?	west				How many feet? 80
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	21	0 Clay			
21	46	0 Sand and sandy clay			
46	47	28 Rock			
47	101	Sand and gravel & clay layers			
101	145	Sand and gravel			
145	158	17 Sand and gravel & rock layers			
158	175	19 Shale			

D