

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County <u>Harvey</u>	Fraction <u>NW 1/4</u> <u>SE 1/4 NW 1/4</u>	Section number <u>32</u>	Township number <u>T 24</u>	Range number <u>S R 3W 1/4</u>
2. Distance and direction from nearest town or city: Street address of well location if in city:		<u>131 W. Patterson</u>		3. Owner of well: <u>Amos Frentz</u> R.R. or street: <u>200 Curtis Street</u> City, state, zip code: <u>Hutchinson, Kansas 67501</u>		
4. Locate with "X" in section below: Sketch map: <u>500 ft. west of center.</u>				6. Bore hole dia. <u>28</u> in. Completion date <u>5-8-77</u> Well depth <u>125</u> ft.		
5. Type and color of material				7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary		
				8. Use: Domestic ☐ Public supply ☐ Industry ☐ ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other ☐		
				9. Casing: Material <u>Transite</u> Height: Above or below Threaded ☐ Welded ☐ Surface <u>12</u> in. RMP ☐ PVC ☐ Weight <u>30</u> lbs./ft. Dia. <u>16</u> in. to <u>86</u> ft. depth Wall thickness: inches or Dia. <u> </u> in. to <u> </u> ft. depth gage No. <u>380 18</u>		
				10. Screen: Manufacturer's name <u>Johnson</u> Type <u>sawed</u> Dia. <u>16</u> Slot/gauze <u>3/16</u> Length <u>39</u> Set between <u>86</u> ft. and <u>125</u> ft. ft. and <u> </u> ft. Gravel pack? <u>yes</u> Size range of material <u>1/8-1/4</u>		
				11. Static water level: <u>13</u> mo./day/yr. <u> </u> ft. below land surface Date <u>2-19-77</u>		
				12. Pumping level below land surfaces: <u>44</u> ft. after <u>1/2</u> hrs. pumping <u>800</u> g.p.m. <u>48</u> ft. after <u>1</u> hrs. pumping <u>1000</u> g.p.m. Estimated maximum yield <u>1400</u> g.p.m.		
				13. Water sample submitted: <u> </u> mo./day/yr. <u> </u> Yes <u> </u> No Date <u> </u>		
				14. Well head completion: <u> </u> Pitless adapter <u> </u> inches above grade		
				15. Well grouted? <u>yes</u> With: <u> </u> Neat cement ☒ Bentonite ☐ Concrete ☐ Depth: From <u>0</u> ft. to <u>10</u> ft.		
				16. Nearest source of possible contamination: ft. <u> </u> Direction <u> </u> Type <u> </u> Well disinfected upon completion? <u> </u> Yes ☒ No		
				17. Pump: Manufacturer's name <u>Jacuzzi</u> Not installed Model number <u>43 1265</u> HP <u>60</u> Volts <u>440</u> Length of drop pipe <u>60</u> ft. capacity <u> </u> g.p.m. Type: <u> </u> Submersible ☒ Turbine ☐ <u> </u> Jet ☐ Reciprocating ☐ <u> </u> Centrifugal ☐ Other ☐		
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Darling Drilling Co.</u> 189 Business name License No. Address <u>1214 W. 4th. Hutchinson, Ks</u> Signed <u>Donald J. Darby</u> Date <u>5-16-77</u> Authorized representative		
Topography: <u> </u> Hill <u> </u> Slope ☒ Upland <u> </u> Valley						