

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		SW 1/4 SW 1/4 SW 1/4	10	T 24 S	R 3 E (W)

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1 mile east and 4 miles south of Burrton

2 WATER WELL OWNER:		City of Wichita	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #		: 455 N. Main	Application Number:
City, State, ZIP Code		: Wichita, KS 67202	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 102 ft. ELEVATION: unknown	
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL not checked ft. below land surface measured on mo/day/yr Pump test data: Well water was not checked ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 155 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Index Well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒	

5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded	
② PVC 4 ABS		7 Fiberglass Threaded	
Blank casing diameter 2 in. to 80 ft., Dia		in. to ft., Dia in. to ft.	
Casing height above land surface 24 in., weight .96		lbs./ft. Wall thickness or gauge No .218	
TYPE OF SCREEN OR PERFORATION MATERIAL:		⑦ PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot ③ Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)	
2 Louvered shutter 4 Key punched 7 Torch cut			
SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 73 ft. to 101 ft., From ft. to ft.			
From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL: ① Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug	
Grout Intervals: From 0 ft. to 58 ft., From ft. to ft., From 58 ft. to 73 ft.	
What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well	11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	13 Insecticide storage None known
3 Watertight sewer lines 6 Seepage pit 9 Feedyard	
Direction from well? How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil			
4	7	Clay, brown			
7	11	Clay, white			
11	60	Sand and gravel, medium, fine			
60	71	Clay, brownish-tan and gray			
71	111	Sand and gravel, medium, fine			
111	116	Clay, green			
116	121	Sand and gravel, coarse, medium, fine			
121	137	Clay, brown and white			
137	142	Clay, red			
142	145	Sand and gravel, medium, fine			
145	153	Shale, weathered, green			
153	155	Shale, green, limey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-17-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 7-27-01 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>	
---	--