


1 LOCATION OF WATER WELL:		Fraction SE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 26	Township Number T 24 S	Range Number R 30 EW
County: Gray Distance and direction from nearest town or city street address of well if located within city? Approximately 5 miles North of Charleston, Ks.					
2 WATER WELL OWNER:		Steve Irsik & Sons			
RR#, St. Address, Box #:		C/O Steve Irsik			
City, State, ZIP Code:		Ingalls, Ks. 67853			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
4 DEPTH OF COMPLETED WELL:		263' ft. ELEVATION: _____			
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
WELL'S STATIC WATER LEVEL ... 159' ft. below land surface measured on mo/day/yr ... 1/20/89.					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield ... 30. gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter ... 11. in. to ... 26.3. ft. and in. to ft.					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No...X..... If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped					
1 Steel		3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)	
2 PVC		4 ABS		7 Fiberglass	
Blank casing diameter 6. in. to ... 263. ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12. in., weight 4.13. lbs./ft. Wall thickness or gauge No. ... 316W					
6 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass 8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile 9 ABS	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot		3 Mill slot		6 Wire wrapped 9 Drilled holes	
2 Louvered shutter		4 Key punched		7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 203' ft. to 263' ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20' ft. to 263' ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0. ft. to 20. ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well					
1 Septic tank		4 Lateral lines		7 Pit privy 11 Fuel storage	
2 Sewer lines		5 Cess pool		8 Sewage lagoon 12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard 13 Insecticide storage	
Direction from well? South How many feet? 75'					
FROM	TO	LITHOLOGIC LOG		FROM	TO
See log attached.					
PLUGGING INTERVALS					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 12/24/88. and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ... 145. This Water Well Record was completed on (mo/day/yr) ... 1/25/89. under the business name of Henkle Drilling & Supply Company, Inc. by (signature) 					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

DRILLERS TEST LOG

CUSTOMER'S NAME: Steve Irsik & Sons
STREET ADDRESS: C/O Steve Irsik Jr.
CITY & STATE: Ingalls, Ks. 67853
COUNTY Gray **QUARTER** NE **SECTION** 26

DATE: 12/21/88
TEST #: 1 E. LOG Yes
DRILLER Shelden
NNSHIP 24 RANGE 30

LOCATION 75' North of Old Well.

HOUSE WELL LOCATION

Z	FOOTAGE			DESCRIPTION OF STRATA	STATIC WATER LEVEL: Proposed Well Depth:	
	From	Pay	To			
	0		2	Top soil.		
	2		61	Brown sandy clay & fine sand streaks & Caliche.		
	61		103	Sand fine to medium coarse. Small to medium gravel.		
	103		124	Brown sandy clay.		
	124		129	Sand fine to medium coarse. Small to medium gravel.		
	129		161	Brown sandy clay.		
60	161	9	170	Sand fine to medium coarse w/streaks of white rock & Clay.		
			201	Brown & gray clay.		
70	201	15	216	Sand fine to medium coarse. Small gravel & white rock.		
	216		217	Brown sandy clay.		
45	217	6	223	Sand fine to small.		
	223		230	Brown sandy clay.		
70	230	31	261	Sand fine to medium coarse. Small gravel w/some white rock.		
			265	Yellow soapstone.		
			280	Weathered shale.		
				Total Depth = 263'		
				6" PVC		
					PLAIN	PERF
				263' - 203'		60'
				203' - 0'	203'	
				TOTAL	203'	60'
				2 - 5 gallon buckets of Bentonite pellets @ 180		
				2 - 50# Bags Hi-Tek		
				6 - 50# Bags Hole plug		
				1 set 4 3/4" Drag Blades		
				1/4 Bit Life on 11" Bit		

GARDEN CITY, KS 67846
3795 West Jones Ave.

HENKLE DRILLING & SUPPLY CO., INC.

316-277-2389

IRRIGATION HEADQUARTERS