	A	- D 14/51 1			ELL RECO	ORD For		KSA 82a		vnship Number	Par	nge Number	7,
	ON OF WATE				NA/	. AIVAZ	% Sec	tion Numbe		<u> </u>	i i	~ aa • # .	
	Fit direction from		town or city stre	, ,	W ½			10	T	24 S	R	02 N	45/
Distance an	ia direction no	nii ileatest	town or city stre				66, Garde	n City KS	3				1
2 WATER	WELL OWNE	R Del	Ray Mounts				· · · · · · · · · · · · · · · · · · ·						
	ldress, Box#			_					Board	d of Agriculture	Division of W	/ater Resource	s
City State	7ID Code	Gar	den City, K	s						cation Number:			
LOCATE	WELL'S LO	CATON W	TH .	-									\neg
	N SECTION E		4 DEPTH	OF COMP	LETED \	WELL	53.0	0 ft. ELI	EVATION:				
			Depth(s) G	roundwate	r Encoun	tered 1	42	2	ft. 2		ft. 3	F	t.
	N		WELL'S ST	ATIC WAT	TER LEV	EL 4	1.52 ft.	below land	surface me	easured on mo	/day/yr 3	/30/2010	- 10
A 13										ho			ה ה
	X									Ho			
	NW	NE	Poro Holo I	Diamotor	8 625	In to	53.	00	Ft and		in to	F	, 9
<u>0</u>		į	- WFLL WAT	FR TO BE	USED A	AS: 5 Pu	blic water s	vlagu	8 Air	conditioning	11 Injection	n well	` !
₩ W			1 Dor	nestic 3	Feed lot	6 Oi	field water	supply	9 <u>De</u>	conditioning ewatering	12 Other ((Specify below)	, <u>.</u>
	İ	!	2 Irria	ation 4	Industria	ol 7 la	um and narr	den (domes	tic) 10 M	Monitoring well	[−] MW-27	'R	
	SW	SE	2 1119		industric	1	wii and gard		10 10 10	No Y	was maldayl	ur nomple wee	
	1	!		nical/bacte	riologica	i sample si	iomitted to i			No X If			
	S		Submitted							Disinfected? Ye			\dashv
5 TYPE O	F BLANK CAS									ING JOINTS: (
1 Ste			MP (SR)	6	Asbesto	s-Cement	9 Other	(specify be	low)	<u> </u>	Welded		
2 PV	С	4 AE	S	7	Fibergla	ss					Threaded	X	
				22	Ft.,							_	
Blank casing	g diameter _	2	In. to	. 33	Dia		In. 1	to	ft., Dia		in. to	ft	.
Casing heig	ht above land	surface	FLUSH	in., w	eight	S	JH 40	Lbs./	ft. Wall thic	kness or gauge	e No.		
TYPE OF S	CREEN OR F	PERFORA	TION MATERIAI							10 Asbestos-c			
1 Ste	el	3 Sta	ainless steel	5	Fibergla	SS	8	RMP (SR)		11 Other (spe-	cify)		
2 Bra			Ivanized steel										1
		TION OPE	NINGS ARE:							cut cut	11 Non	e (open hole)	
	ntinuous slot		3 Mill slot				rapped			ed holes			
2 Lou	uvered shutter	7	4 Key punche			7 Torch			10 Oth	er (specify)			
SCREEN-P	ERFORATED	INTERVA		33									
			From		ft	. to		ft.	From		ft. to	F	t.
SAN	ND PACK INT	ERVALS:	From	31	ft	. to	53	ft.	From		ft. to	F	t. 1
			From			. to					ft. to		t.
6 GROUT	MATERIAI ·	1 Ne	eat cement	2 Cem	ent arou	t	3 Ben	tonite	4 Other				
				F	₹t.		Ft.						
Grout Interv	als From2	5	ft. to	29 F	rom3	29	to	3	1 ft.	From			
What is the	nearest sourc	e of possit	ole contaminatio	n:				10 Live	stock pens	14	Abandoned v	water well	
1 Sep	otic tank		4 Lateral I	ines	7	Pit privy		11 Fue	l storage	15	Oil well/ Gas	well	
2 Sev	wer lines		5 Cess po	ol	8	Sewage I	agoon	12 Fert	tilizer storaç	ge 16	Other (speci	fy below)	
3 Wa	tertight sewer	lines	6 Seepag	e pit	9	Feedyard		13 Inse	ecticide stor	age	Contamin	ated Site	_
Direction fro						, , , , ,		How man	y feet?	Ü			
FROM	то	CODE	LI	THOLOGIC	CLOG		FROM	ТО		PLUGGIN	IG INTERVAL	S	\neg
0	.5	1	Asphalt and					+					\dashv
.5	5		Silty clay, li										\dashv
5	8		Sandy Clay			ined							
8	40		Sand, fine-ı										\dashv
40	53		Sand, loose										
53	TD		END BORE										
													_
-100:	0705:5	1.41.15.51	VEDIC CETT	OATIO	T L:		(-)	10 1 (0)		(0) -1		i- 4!-4!	
			NER'S CERTIFI	CATION:	This wate	er well was	(x) constru						
	on (mo/day/yr		3	30/2010	. <u>.</u>	· 	And th			best of my kno			
Water Well	Contractor's L	icense No		50	50		This V	Vater Well F	Record was	completed on	(mo/day/yr)	4/16/2010	
under the bu	usiness name	of	Asso	ciated E						ure) Bradle			
			anks and circle th 913-296-5545.							and Environmer	nt, Burgau of W	ater Topeka,	
Nansas	00020-0001.	· elebrione:	913-2 3 0-3343. 3	Jenu One 10	WIEK	VALLE OVAIN	LIX dilu retal	i one loi you	ui iecolus.	1.2000	Sect for	usa	\dashv
							- ,			(111		_