		RECORD		WWC-5			esources; App. No. F1-18	
1 LOCAT	TION OF	WATER WELL: Finney	Fraction NE 4	NW ½	NE 1/4	ection Numbe	r Township Number	Range Number R 33 EW
County: Finney NE ½ NW ½ NE ½ Distance and direction from nearest town or city street address of well if located within city? From Holcomb, appx 1 1/2 miles South & 2 Miles East County: NE ½ NB ½ NE ½ Clobal Positioning System (decimal degrees, min. of 4 digits)								
		OWNER: Dick W	/ebdell	·····		levation:		
RR#, St.	. Address,	Box # : Box 10 ode : Holcon	8 ab Ks 67851			Datum: Data Collection	Method:	
		'S 4 DEPTH OF				CONCOUNT	ft.	
LOCAT						***************************************		
	AN "X" I	N Depth(s) Groun	ndwater Enco	ountered 1		ft.	2 ft. 3	ft.
	ON BOX:	WELL'S STAT	TIC WATER	LEVEL	138 ft.	below land su	2 ft. 3 rface measured on mo/d	lay/yr 7/22/08
X	N	Pump	test data:	Well water	was 17	5 ft. after	4 hours pump	ing 1500 gpm
	X	Est. Yield	gpm:	Well water	was	ft. after	4 hours pump hours pump	ing gpm
⊢vw-		WELL WATE	R TO BE US	SED AS: 5		8.	Air conditioning 11 Inewatering 12 Oth	njection well
w		E Domestic 3	reed lot 6	Oil field ' Domestic	water supply	y 9D6 ordon) 10M	ewatering 12 Oth onitoring well	er (Specify below)
L _{GW} -		E in rigation 4	muusu iai	Domesuc	(lawii & ga	ruen) io wi	omtoring wen	
SVV	J.	Was a chemica	l/bacteriolog	ical sample	submitted	to Department	t? Yes No x;	If ves. mo/day/yrs
<u> </u>	S	Sample was sul	bmitted			Water	Well Disinfected? Yes	x No
5 FYPE (OF CASI	NG USED: 5	Wrought Iro	n	8 Concrete	tile CA	ASING JOINTS: Glued	Clamped
1 Stee	1	3 RMP (SR) 6	Asbestos-Co	ement	9 Other (sp	pecify below)	Welde	d X
2 PVC		4 ABS 7	Fiberglass	ъ.			Threa	ded
Blank casin	ig diamete	r 16 in. to	350 ft.	., Dia	in	. to	It., Dia in.	to II.
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 16 in. to 350 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., Weight 42 lbs./ft. Wall thickness or gauge No250 TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
2 Bras	ss 4 Gal	vanized steel 6 Co	ncrete tile	8 RM (SR) 10 As	bestos-Cemen	t 12 None used (ope	n hole)
2 Lou	vered shut	ter 4 Key punche	d 6 Wire	wrapped	8 Saw C	tut 10 Ot	ther (specify)	(open note)
Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 186 ft. to 296 ft. From 315 ft. to 345 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 350 ft. From ft. to ft. From ft. to ft. From ft. to ft.								
GRA	GRAVEL PACK INTERVALS: From 20 ft. to 350 ft. From ft. to ft.							
			From		ft. to	ft.	From ft. t	o ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite 4 Other								
Grout Intervals From 0 ft. to 20 ft. From 5 0 ft. to 60 ft. From ft. to ft.								
		ource of possible cor			10.1.			16.001 6 10
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage (14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well								
Direction fr					How many	_		
FROM	TO	LITHO	LOGIC LOG	<u>-</u>	FROM	ТО	PLUGGING INTI	ERVALS
0		Top soil						
3 20	20 47	Sand fine, med coa Sand fine to med c						
47	55	Clay sand med to			1			
55	70	Clay ledges						
70	95	Clay sticky						
95 105	105 120	clay Clay sticky						
120	130	clay						
130	137	Sand fine to med c	oarse					
137 155	155 162	Clay rock Sand fine clay					AND THE RESERVE OF THE PERSON	
162	175	Clay, sand	A.L. 4 4					
175	179	Sand fine clay						
179		Clay rocks						
186 205	205 230	Sand fine to med c Sand fine to med c						
White (Same into to mod t		KSA	82a-1212			- T (84 t) 545 5 150
	•						man ha malla	740 0400

230	245	Sand fine to med coarse
245	260	Sand fine to med coarse
260	276	Sand fine to med coarse
276	280	Clay limerock
280	296	Sand fine to med coarse
296	315	Clay sticky
315	326	Sand fine to med coarse gravel
326	345	Sand fine to med coarse
345	370	Clay sticky
370	375	Soapstone yellow hard
375	380	shale
	<u> </u>	
		'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged
		and was completed on (mo/day/year) 07/18/08 and this record is true to the best of my knowledge and belief.
Kansas Wa	ter Well Co	ontractor's License No145 This Water Well Record was completed on (mo/day/year)08/08/08
under the b	usiness nan	ne of Henkle Drilling & Supply Co, Inc. by (signature) but flechmuff.
Geology Sec	tion, 1000 S	se fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, W Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for 0 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.