USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

							Г			
T	R	EW	sec	1/4	1/4	1/4	Νo			
0/0	Kansas State Dept. Of Healt									
~\'\mathre	(Water Well Contractors)									
6 111.		Fort	es-Bld	g. 74	10					

						י עי		opeka, Kansas ooozu	
County 1 Location of well:	Township name	Fraction		Section	on number	24	Town number	Range number	
Finney		SW, N	E, S		25	~ /	245	34W	
Distance and direction from nearest town or ci	2 Miles sout	th and	3 Owne	r of well	LOIG		Mader		
Street address of well location if in city: 3/	4 mile west o	of s	Addr	ess:	R.R.	eland, Kansas			
Locate with "X" in section below:	Sketch map:				•	4 Well depth: 422 ft. Date of completion			
N .	Well drilled	near ¶	H 16	- 75			II diameter _28 in.	Drives D Due	
at the center of the SW4, Sec.				5 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary					
24, T24S, T34W, Finney County,					6 Use: Domestic Public supply Industry				
W	Kansas					frigation Air conditioning Commercial Test well			
X						7 Casing: Material Stl Height: above/below Threaded Welded Sufface 12 in. Diam. Weight 18 lbs./ft.			
<u> </u>									
1 Mile		_	-			1	6 in. to 176. depth [Drive shoe? Yes XNo	
2 Тур	e and color of material			From	To	8 Scr	in. to ft. depth		
n· 1					40		nufacturer Foste L slot & lou	r & Brown	
Fine sand				0	42	1 1 1	De 1	ength 246	
Coarse sand fine grav	rel			42	70	Set	between 176 ft. and	422 ft	
Fine to coarse sand f	fine gravel cl	lay str	eaks	70	220	l	tings: 1 2 m avel pack X Yes No	m to 5.5 mm Size range of material	
Tan clay sand streaks	3			220	270		tic water level: 100 . below land surface	e Date <u>10</u> _11_75	
Fine to coarse sand s	some clay lens	ses		270	300		nping level below land sur	faces: . pumping 1080g.p.m.	
Fine to coarse sand f	fine gravel			300	422	1.	57 ft. after 1 hrs. mated maximum yield 20	. pumping <u>140</u> 4g.p.m.	
Hard tan clay				422	440	11 Wa	ter sample submitted:		
							X esNo Date II head completion:	<u> </u>	
						_	,	Inches above grade	
							II grouted? 🄀 Yes Neat cement 🛣 Bentoni	□ No	
							oth: From _O_ft. to .		
						14 Ne	arest source of possible co		
						We	Il disinfected upon comple		
						15 Pun	np: [nufacturer's name_Lay	Not installed	
						Мо	del number 12K	HP 100 Volts 480	
						Ler Typ		ft. capacity 800 _{g.m.p.}	
							Submersible	X Turbine	
(use	a second sheet if needed)					_ =	Jet [Certrifugal [Reciprocating Other	
16 Remarks: elevation	-					l	ter well contractor's certif		
						l	s well was drilled under my ort is true to the best of m	′ ·	
Topography:						<u></u>	Layne-Wester	n Co. Inc. 150	
x Hill ☐ Slope							iness name dress Box 686	Garden City.	
Upland						Sig	ned Authorized represe	infante Uate	
☐ Valley					-			20 Nor	

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5