WATER WELL RECORD	Form V	VWC-5	Division of Wate	er Resources App. No.	23,640				
1 LOCATION OF WATER WELL:	Fraction Near	Center		Township No.	Range Number				
County: FINNEY	1/4 1/4	1/4 NW 1/4	Clabal Parities		R 34 □E ▼W				
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here									
South side of Holcomb- Across bridge - 2 miles			Longitude:						
south, 3,865 Ft. North & 3,935 Ft. West		Elevation:							
2 WATER WELL OWNER: Eugene L. & Connie J. Gross			Datum: WGS 84, NAD 83, NAD 27 Collection Method:						
RR#, Street Address, Box #: 15 S. Holcomb Lane			GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey						
City, State, ZIP Code : Holcon	ıb, Kansas 678	351		noto, ☐ Topographic S m, ☐ 3-5 m, ☐ 5					
3 LOCATE WELL		4.2			, 13 m,				
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 425 ft.									
SECTION BOX: Depth(s) Groundwater Encountered (1)									
Pump test data: Well water wasft. afterhours pumpinggpm									
EST. YIELD									
WELL WATER	Bore Hole Diameter30								
Sw. SF. Domestic	Demostic Descript Doll field water spenky Developing Dethor (Specify below)								
Irrigation	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes X No If yes, mo/day/yr sample was submitted									
	fected? Tyes								
5 TYPE OF CASING USED: X Stee									
CASING JOINTS: Glued Clar	nped 🛛 Welded	☐ Threaded							
Casing diameter 1.6 in. to 28	0 ft., Diameter	in.	to ft., D	Diameter	in. to ft.				
Casing height above land surface		nt 	lbs./It., wall thi	ckness or gauge No.	• 230				
▼Steel Stainless Steel PVC Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From									
SCREEN-PERFORATED INTERVALS:	From280	. ft. to4	25 ft., From	ft. to	o ft.				
GRAVEL PACK INTERVALS:	From20	. ft. to4	25 ft., From	ft. to	o ft.				
	From	. ft. to	ft., From	ft. to	o ft.				
6 GROUT MATERIAL: Neat ceme Grout Intervals: From0 ft. to					ft to ft				
What is the nearest source of possible contained		ли	11. 10 11.,	, riom	11. 10				
	nes Pit privy	Livestock			r (specify below)				
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well									
Direction from well North									
FROM TO LITHOLOG	IC LOG	FROM	TO LITHO. L	OG (cont.) or PLUC	GGING INTERVALS				
See attached	log								
7 CONTRACTOR'S OR LANDOWNEI	C'S CERTIFICATI	ON: This wate 8-30-11	er well was X construction	ructed, reconstru	cted, or plugged				
under my jurisdiction and was completed on (mo/day/year)8-30-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)8-31-11									
under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Morw Heller									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.									
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									

The Professionals MINTER-WILSON DRILLING CO. Irrigation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

GENE GROSS

COUNTY

FINNEY

DATE

7-25-11

LOCATION:

NW 1/4 24-24-34 - THIRD CIRCLE SOUTH OF MINTER-WILSON SHOP

- 100 FT. SOUTH OF PIVOT

STATIC WATER LEVEL - 230 FT.

TEST #1

0' TO 6'	- F	INE	SAN	ID
----------	-----	-----	-----	----

6' TO 19' - FINE TO MEDIUM SAND & GRAVEL

19' TO 43' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

43' TO 49' - FINE TO MEDIUM SAND & GRAVEL

49' TO 57' - BROWN SANDY CLAY

57' TO 65' - FINE TO MEDIUM SAND & GRAVEL

65' TO 93' - BROWN SANDY CLAY WITH LAYERS OF SAND & GRAVEL

93' TO 193' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL

193' TO 200' - FINE TO MEDIUM SAND & GRAVEL

200' TO 230' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL

230' TO 245' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY - 30%

245' TO 263' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

263' TO 266' - FINE TO MEDIUM SAND & GRAVEL

266' TO 277' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

277' TO 282' - FINE TO MEDIUM SAND & GRAVEL

282' TO 285' - BROWN SANDY CLAY

285' TO 287' - FINE TO MEDIUM SAND & GRAVEL

287' TO 300' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 10%

300' TO 311' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

311' TO 316' - BROWN SANDY CLAY

316' TO 343' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 15%

343' TO 350' - BROWN SANDY CLAY

350' TO 353' - FINE TO MEDIUM SAND & GRAVEL

353' TO 355' - BROWN SANDY CLAY

355' TO 357' - FINE TO MEDIUM SAND & GRAVEL

357' TO 361' - BROWN SANDY CLAY

361' TO 394' - FINE TO MEDIUM SAND & GRAVEL

394' TO 408' - BROWN & YELLOW CLAY, WHITE ROCK, SAND & GRAVEL & BROWN ROCK MIXED - TOOK WATER

408' TO 420' - HARD BROWN & YELLOW CLAY WITH 15% BROWN ROCK - 300 PULL DOWN

420' TO 440' - SHALE - 300 PULL DOWN