WATER WELL RECO	RD	Form W	WC-5	Division of Wat	er Resources App. N	13,202
1 LOCATION OF WATE		Fraction		Section Number	Township No.	Range Number
County: FINNEY Street/Rural Address of Well Location;		4 SE 1/4 NW		20	T 24 S	R 34 □E ☑W
			g System (GPS) in			
from nearest town or intersection: If at owner's address, check here  S. SIDE OF HOLCOMB-4 MILES WEST, 2 MILES SOUTH,				Latitude: (in decimal degrees) Longitude: (in decimal degrees)		
3,970 FT. NORTH & 1,415 FT. WEST				Elevation:		1
2 WATER WELL OWNER: TYSON FRESH MEATS, INC.				Datum: WGS 84, NAD 83, NAD 27 Collection Method:		
RR#, Street Address, Box #: 800 STEVENS PORT DRIVE				GPS unit (Make/Model:)		
City, State, ZIP Code : DAKOTA DUNES, S.D. 57049				Digital Map/Photo, Topographic Map, Land Survey  Est. Accuracy: S m, S -5 m, 5 -15 m, > 15 m		
3 LOCATE WELL						3-13 m,   2-13 m
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 410 ft.  SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.						
SECTION BOX: Depth(s) Groundwater Encountered (1)						
Pump test data: Well water wasft. after hours pumping						
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm						
W   E   Bore Hole Diameter .30in. to						
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No  If yes mo/day/yr sample was submitted						
S If yes, mo/day/yr sample was submitted						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Gh	ied	nped Welded	☐ Threaded			
Casing diameter 16 in to 280 ft. Diameter in to ft. Diameter in to ft.						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:   V   Steel						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot  Mill slot  Gauze wrapped  Torch cut Drilled holes  None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From 280 ft. to 410 ft., From ft. to ft.						
From ft. to ft., From ft. to ft. oft. GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From 140 ft. to 410 ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: ☐ Neat cement						
Grout Intervals: From	Z ft, to	o	n .00	ft. to! <del>4.</del> 9 ft	., From	. ft. toft.
What is the nearest source of possible contamination:  Septic tank  Lateral lines Pit privy  Livestock pens  Insecticide storage  Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage  Abandoned water well						
Direction from well SOL	JTHEAST	pit Feedyard	☐ Fertilizer st	orage		
FROM TO	LITHOLOG	HC LOG	FROM			JGGING INTERVALS
CEE ATT	VCIIED I OC					
SEE ATTA	ACHED LOG					
				44		
				the state of the s		THE CONTRACT OF THE CONTRACT O
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year)1-20-12 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year) .1-23-12						
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterwell/ii		PREMIUM 1994 1994 1994 1994 1994 1994 1994 199				
KSA 82a-1212				Check: 📝 V	Vhite Copy, 🔲 B	lue Copy, 🔲 Pink Copy

## MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Domestic and Repairing

**INCORPORATED** 

**GARDEN CITY, KANSAS 67846** Phone 620-276-8269 P.O. Box A

NAME

TYSON FRESH MEATS

COUNTY

FINNEY

DATE

10-17-11

LOCATION:

NE 1/4 20-24-34 - SOUTH OF KLOTZ TO 1ST TURN, 1/2 MILE WEST,

1/4 MILE NORTH & 1/4 MILE EAST

- 115 FT. WEST OF PIVOT

STATIC WATER LEVEL - 75 FT.

## TEST#1

0' TO 3' - FINE LOOSE SAND

3' TO 7' - BROWN SANDY CLAY

7' TO 24' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

24' TO 32' - BROWN SANDY CLAY

32" TO 44' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

44' TO 63' - BROWN SANDY CLAY

63' TO 79' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

79' TO 95' - BROWN CLAY

95' TO 135' - BROWN CLAY WITH STRIPS OF SAND & GRAVEL

135' TO 272' - BLUE CLAY

272' TO 291' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH STRIPS OF BROWN SANDY CLAY - 15%

291' TO 297' - BROWN SANDY CLAY

297' TO 329' - FINE TO MEDIUM SAND & GRAVEL

329' TO 334' - BROWN SANDY CLAY

334' TO 372' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

372' TO 393' - FINE TO MEDIUM SAND & GRAVEL - TIGHT

393' TO 397' - FINE TO MEDIUM SAND & BROWN ROCK

397' TO 402' - HARD BROWN & YELLOW CLAY WITH 10% BROWN ROCK

402' TO 410' - SHALE - 250 PULL DOWN