WATER WELL OWNER: LEWIS M	 IOL7	
RR#, St. Address, Box # : RFD	Board of Agriculture, Division of Water Resour	ces
City, State, ZIP code : DEERFIE	ELD, KS 67838- Application Number: KE - 04	
	(4 DEPTH OF COMPLETED WELL 251 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 95 ft. 2. 0 ft. 3.	0 ft.
\	WELL'S STATIC WATER LEVEL 95 ft. below land surface measured on mo/day/yr 04 Pump testdata: Well water was 0 ft. after 0 hours pumping	1/15/92 0 gpm
, ,	Estimated Yield O gpm: Well water was O ft. after O hours pumping	Ogpa;
i W	E Bore Hole Diameter in. to 0 ft., and in. to 0 ft.	6 1
S#		3 E 8
		,
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE	: UNKNOWN	ted? Yes
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE	EL CASING JOINTS: WELDED In. to 0 ft., Dia in. to 0 ft., Dia in. to 0 ft. -72 in., weight 0 lbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL E: UNKNOWN From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.	ted? Yes
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT	CASING JOINTS: WELDED In. to 0 ft., Dia in. to 0 ft., Dia in. to 0 ft. -72 in., weight 0 lbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL UNKNOWN From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.	ted? Yes
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS:	CASING JOINTS: WELDED In. to Oft., Dia in. to Oft., Dia in. to Oft. -72 in., weight Olbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL UNKNOWN From Oft. to Oft., From Oft. to Oft.	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss	CASING JOINTS: WELDED In. to Oft., Dia in. to Oft., Dia in. to Oft. -72 in., weight Olbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL : UNKNOWN From Oft. to Oft., From Oft. to Oft. Sible contamination: NONE OBSERVED	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well?	CL CASING JUINTS: WELDED In. to 0 ft., Dia in. to 0 ft., Dia in. to 0 ft. -72 in., weight 0 lbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL : UNKNOWN From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. Sible contamination: NONE OBSERVED How many feet	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well?	CASING JOINTS: WELDED	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well?	L CASING JOINTS: WELDED In. to 0 ft., Dia in. to 0 ft., Dia in. to 0 ft. -72 in., weight 0 lbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL E: UNKNOWN From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. Etc 15 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. Sible contamination: NONE OBSERVED How many feet LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 5 TOPSOIL 5 15 CEMENT GROUT	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well?	CASING JOINTS: WELDED	
TYPE OF BLANK CASING USED: 01 STEE Blank casing diameter 16 i Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUT Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well?	L CASING JOINTS: WELDED In. to 0 ft., Dia in. to 0 ft., Dia in. to 0 ft. -72 in., weight 0 lbs/ft. Wall thickness or gauge No. ERIAL: 01 STEEL : UNKNOWN From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. Sible contamination: NONE OBSERVED How many feet LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 5 TDPSOIL 5 15 CEMENT GROUT 15 95 CLAY 95 251 CHLORINATED SAND 0 0	