


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 26 Township Number T 24 S Range Number R 35 EW

Distance and direction from nearest town or city street address of well if located within city?  
 Deerfield: East side 3 South 1/2 West and South into

2 WATER WELL OWNER: EOG Resources Inc. Zrubek #1  
 RR#, St. Address, Box # : 3817 NW Expressway Ste. 500 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code : Oklahoma City, Ok 73112 Application Number: 80050091

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL 220 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1 35 ft. 2 ft. 3 ft.  
 WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 3-18-05  
 Pump test data: Well water was 48 ft. after 1 hours pumping 80 gpm  
 Est. Yield 80 gpm: Well water was ft. after hours pumping gpm  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well  
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 9 Dewatering 12 Other (Specify below)  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded  
 Threaded  
 Blank casing diameter 6 in. to 220 ft., Dia in. to in. to in. to in. to  
 Casing height above land surface 24 in., weight 4.074 lbs./ft. Wall thickness or gauge No. SDR 31  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement  
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 160 ft. to 220 ft., From ft. to ft. to ft. to ft.  
 GRAVEL PACK INTERVALS: From 80 ft. to 220 ft., From ft. to ft. to ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug  
 Grout Intervals: From 1 ft. to 25 ft., From ft. to ft. to ft. to ft. to ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? Southeast How many feet? 350

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay			
2	5	Sand			
5	7	Clay			
7	54	Sand and gravel			
54	73	Clay			
73	88	Sandy clay			
88	130	Clay "blue"			
130	139	Sand			
139	142	Clay "tan"			
142	160	Sand and sandy clay			
160	210	Sand			
210	220	Sand and clay streaks			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. KWCL-430 This Water Well Record was completed on (mo/day/yr) 3-18-05 under the business name of Howard Drilling Co Box 806 Beaver, Ok 73932 by (signature) Howard