


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Kearny	Township name	Fraction SE 1/4 SW 1/4	Section number 30	Town number 24	Range number 35
Distance and direction from nearest town or city: 1 mi South, 1 1/2 mi East of Lakin, Ks. Street address of well location if in city:				3 Owner of well: Van River Cattle c/o Phil VanDoren Address: 809 N 6, Garden City, Ks. 67846		
Locate with "X" in section below: 				Sketch map:		4 Well depth: 336 ft. Date of completion 7-26-75 Well diameter 26 in.
2				Type and color of material		5 <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
						6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well
						7 Casing: Material Steel Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16" Weight 219 lbs./ft. 0 in. to 336 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No 0 in. to 0 ft. depth
						8 Screen: Manufacturer W A Brown Enterprises Type Millslot Dia. 16" Slot/gauze 1/8 Length 1" Set between 96 ft. and 176 ft. Fittings: 256 336 1x5/8 Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material
						9 Static water level: 18 ft. below land surface Date 7-26-75
				10 Pumping level below land surfaces: 80 ft. after 5 hrs. pumping 2000 g.p.m. 0 ft. after 0 hrs. pumping 0 g.p.m. Estimated maximum yield 2000 g.p.m.		
				11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
				12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> Inches above grade		
				13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No ### <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From 0 ft. to 10 ft.		
				14 Nearest source of possible contamination: NA ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
				15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Worthington Model number 15H226 HP Volts Length of drop pipe 333 ft. capacity 2200 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
16 Remarks: elevation Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland Level <input type="checkbox"/> Valley				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. High Plains Drilling & Supply, Inc 136 Business name License No. Address 102 N 3rd, Garden City, Ks. Signed Scott E. ... Date 7-26-75 Secretary Representative		

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5