	WATE	R WELL RE	ECORD	Form W	WC-5 KSA 8	a-1212 MW-5				
LOCATION OF WATER WELL:	Fraction 1/4	NE		₩ <sub>1/4</sub>	Section Number 27		hip Number 24 s	R	ange Nun	nber E(W)
Distance and direction from nearest to		ddress of w	vell if locat			<del></del>	23 3		36	_=(٧٧)
						-		<del></del>		
WATER WELL OWNER: RR#, St. Address, Box #4821 Mex	6 Company C/ xico Gravel	0 Marg	aret S	pellma	an		d of Agriculture			Resource
							cation Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	Depth(s) Ground	OMPLETED water Enco	o WELL untered	20 22 - 1	3	/ATION: . 2 <del></del>	<del> </del>	<del></del> 3 <del>-,</del> -	· · · · · · · · · · · · · · · · · · ·	
· X	WELL'S STATIC	WATER LE	EVEL . [7]	1.1.2.5.	. ft. below land s	surface measure	ed on mo/day/y	r		
NW NE	Est. Yield						•			•
<u></u>	Bore Hole Diame	ter 8.6	25in. to	28		, and <del></del> -	i	n. to		
E W ! ! ! !	WELL WATER TO				water supply		oning 11			
- 1	1 Domestic	3 Fe	edlot	6 Oil fie	ld water supply	Dewaterin	g h 12	Other (S	Specify be	low)
	2 Irrigation		dustrial		and garden only					
	Was a chemical/b	pacteriologic	cal sample	submitted					•	e was su
TYPE OF BLANK CASING USED:	mitted	5 Wrough	ıt iron	8 (		Vater Well Disir CASING			No X	1
1 Steel 3 RMP (S	SR)	_			Other (specify be				<u>.</u>	
(2) PVC 4 ABS	,–	7 Fibergla			· · · · · · · · · · · · · · · · · · ·	•			_	
Blank casing diameter2	in. to	ft., C	Dia							
Casing height above land surface		in., weight	s	CH 40	EVC lb:	s./ft. Wall thick	ness or gauge	No <u>.</u> .		
TYPE OF SCREEN OR PERFORATION					7)•VC		Asbestos-cen			
1 Steel 3 Stainles	s steel	5 Fibergla	ass		8 RMP (SR)		Other (specify			
2 Brass 4 Galvani		6 Concret			9 ABS		2 None used (d			
SCREEN OR PERFORATION OPENII				zed wrapp		8 Saw cut		11 No	ne (open	hole)
	Mill slot			wrapped		9 Drilled h				
	Key punched	7		ch cut Z		•	pecify)			
SCREEN-PERFORATED INTERVALS					./ ft., Fi					
らかり G <del>RAVE</del> L PACK INTERVALS	From	<del></del>	π.το.	76	ft., Fi	rom	π. <del></del> -	το		۱۱
GHAVEL PACK INTERVALS	From	٠٠٠٠٠٠٠	Tt. to					to		!! fi
GROUT MATERIAL: 1 Neat		Cement				4 Other				•
Grout Intervals: From	ft. to 14			4					· · · · · · · · · · · · · · · · · · ·	
What is the nearest source of possible	. ,			.,		estock pens			ed <del>wate</del> r v	
1 Septic tank 4 Late		7 F	Pit privy			el storage				
2 Sewer lines 5 Ces		8 Sewage lagoon				tilizer storage	_	16 other (specify below)		w)
3 Watertight sewer lines 6 See	•		eedyard	•		ecticide storage		,		
Direction from well?			_		How n	nany feet?	Contar	minate	d Si	
FROM TO	LITHOLOGIC I	LOG		FRO	ОМ ТО		PLUGGING	INTERV	ALS	
OT 100 D										
GL 1.00 Driveway				<b>-</b>						
1.00 25.50 Silty Cla			<del></del>							
5.50 28.00 Sand (SP) 3.00 TD End of bo						<u> </u>				
3.00 TD End of bo	rehole									
						<u> </u>				
						<del> </del>				
				1	1	1				
				<del>-  </del>		Flush Mou	nt			
						waiver				
						D. Taylor				
CONTRACTOR'S OR LANDOWNE	D'S CEDTIEICATI	ON: This	rator well:	Was /1V~		<del></del>	96 plugged	nder my i	uriediction	and wa
CONTRACTOR'S OR LANDOWNER completed on (mo/day/year) $\dots$ 3.	.n 3 CENTIFICATION - 6 - 97	ON: Inis w	aler Well \	was (ILCC	and this as					
Vater Well Contractor's License No.						cord is true to t			anu D <del>e</del> lle	zi. r\all58
1 11: 1 : 1	285		iis vvaler	TEU NECO		nature)	/ - /	, 1		<b>1</b>
	PLEASE 22522 5	IDM V 50	IAIT oleaste 5	Diagram Ell 1- 1			7	2000000	Kanasa Di	orden and
INSTRUCTIONS: Use typewriter or ball point of Health and Environment, Bureau of Water	r, Topeka, Kansas 66620	0-0001. Teleph	ne: 913-296	isase iii iri ( i-5545. Send	one to WATER WELL	OWNER and retain	nors, send topulate one for your recor	ds.	панвав пер	arun <del>e</del> ni