

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

2482

1 LOCATION OF WATER WELL: County: Kearny Fraction: NW 1/4 SE 1/4 NW 1/4 Section Number: 33 Township Number: T 24 S Range Number: R 36 EW

Distance and direction from nearest town or city street address of well if located within city? Lakin South Side-1 Mile South, 3/4ths of a Mile West, 3,650 Ft. North & 3,935 Ft. West Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Robert Beymer RR#, St. Address, Box #: PO Box 363 City, State, ZIP Code: Lakin, KS 67860 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW quadrant] 4 DEPTH OF COMPLETED WELL: 300 ft. Depth(s) Groundwater Encountered: WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr: 12-5-07 Pump test data: Est. Yield: WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted. Water well disinfected? Yes No X

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass CASING JOINTS: Glued Clamped Welded XX Threaded Blank casing diameter: 16 in. to 130 ft., Diameter: Casing height above land surface: 12 in., Weight: 42.05 lbs./ft. Wall thickness or gauge No.: 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 130 ft. to 300 ft. GRAVEL PACK INTERVALS: From 60 ft. to 300 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 60 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? Northeast How many feet? 100 ft. north & 65 ft. east

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Content: See attached log

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-10-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 1-4-08 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.

The
Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Beymer
Kearny County
10-16-07

Location: NW $\frac{1}{4}$ 33-24-36 - Lakin River Road - 3/4 of a mile west on the
north side - 100 ft. south of existing well

Static Water Level - 30 ft.

Test #2

0' to 2' - Top soil
2' to 6' - Brown sandy clay
6' to 10' - Fine to medium sand & gravel
10' to 28' - Brown clay
28' to 44' - Fine to medium sand & gravel
44' to 59' - Brown clay
59' to 74' - Blue clay
74' to 78' - Brown clay
78' to 89' - Fine to medium sand & gravel
89' to 113' - Brown clay
113' to 149' - Fine to medium sand & gravel
149' to 157' - Brown clay
157' to 180' - Fine to medium sand & gravel
180' to 189' - Brown clay
189' to 204' - Brown sandy clay
204' to 209' - Fine to medium sand & gravel
209' to 250' - Brown clay
250' to 279' - Fine to medium sand
279' to 286' - Brown sandy clay
286' to 293' - Fine to medium sand & fine gravel
293' to 297' - Brown clay
297' to 302' - Brown clay with brown rock mixed - tight
302' to 305' - Brown yellow clay (Lost circulation)