VATE	R WEL	RECORD Form WWC	-5	Division of Wa	er Resources; App. No.	
		Fraction SW 1/4	F 17	Section Number		Range Number
	ity: Kearr					
Distance and direction from nearest town or city street uddress of well if Global Positioning Systems (decimal degrees, min. of located within city? 516 N. Main. Lakin.						ices, min, or 4 digits)
located within city? 616 N. Main, Lakin				Longitude: 101.26764		
2 WATER WELL OWNER: Presta OII				Elevation: TOC 3006.54		
		ss, Box # : 14008 Reeder St.		Datum:		
	, State, ZI	•			MAL-J. COE	***************************************
Data Conection Method, SF3						
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL35						
LOCATION						
SECTION BOX: WELL'S STATIC WATER LEVEL 26.50						
N Pump test data: Well water was						
Est. Yieldgpm: Well water was						
		WELL WATER TO BELIEFE AS & O.L.	lic water	supply 8 Air	conditioning Ini	ection well
W 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-7R						
1 Was a chemical/hasterial roughly submitted to Department? Vac No V · If yes mo/day/we						
Sample was submitted						
	S					
TYPI	E OF CAS	ING USED: 5 Wrought Iron 8 Con	rete tile	CASIN	G JOINTS: Glued	Clamped
1	Steel	3 RMP (SR) 6 Asbestos-Cement 9 Othe	r (specif	y below)	Welded	·····
2	PVC	ING USED: 5 Wrought Iron 8 Cont 3 RMP (SR) 6 Asbestos-Cement 9 Othe 4 ABS 7 Fiberglass	*******	· · · · · · · · · · · · · · · · · · ·	Threaded	
Blank casing diameter						
asing t	neight abo	e land surface in., Weight		lbs./ft. Wall th	ickness or guage No.	Sch 40
YPE (F SCREE	N OR PERFORATION MATERIAL:				
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 0.010 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 20						
From						
GRAVEL PACK INTERVALS: From. 18						
		From				
		ERIAL: 1 Nent cement 2 Cement grout 3 Be	ntonite	4 Other Come	nt 0.5-1.5'	
	itervals:	From1.5 ft. to18 ft., From		. N. to	N., From	ft. to
What is the nearest source of possible contamination;						
	Septic tan		10 Lives	tock pens 13 in	secticide Storage	16 Other (specify
	Sewer line	s 5 Cess pool 8 Sewago-tagoon [Truel s	torage 14 A	bandoned water well	below)
	watertigh	be were the enclosed by the state of the sta				***************************************
ROM	TO	LITHOLOGIC LOG			PLUGGING INT	
U	0.5	Gravel LithOLOGIC LOG	FROM	* 10 	PLUGUING IN I	CKYNLS
0.5	20	CLAY	+			
20	23					
	26	CLAY with gravel	 			
23 28	35	SAND with clay	 			
	 					
	 		+			
						
	 					
T CONTRACTORIS OR LANGUAGE CONTINUES AND THE CONTRACTORIS OF THE C						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged						
under my jurisdiction and was completed on (mo/day/year) 9-28-14						
under the business name of Woofter Pump & Well by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or titcle the officer and for						
uce copi	cs to Kanses	Department of Health and Environment, Bureau of Water, Gook	gy Section	, 1000 SW Jackson St.,	Suite 420, Topeka, Kansas	66612-1367. Telephane
R5-296-5	522. Sen	d one to WATER WELL OWNER and retain one fo	your i	records. Fee of \$5	.00 for each constructed	well. Visit us a
ttp://www	w.kdhe.sune.	ks.us/geo/watenvells				