USE_TYPEWRITER OR BALL POINT REN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction			T	Section number		Township number Range number				
1. Location of well:	KEARNY	NE 1/4 NN/4 NE 1/4		/4	T 21, s			R 37	E M			
	ction from nearest town or city: 3 V	est 3	north	3	. Owne	er of well		ton Beymer				
Single dudies of well location if in city:								akin, Ks. 67860				
City, state, zip code:								6. Bore hole dia. 26 in. Completion date 5–21–76				
4. Locate with "X" in section below: Sketch map:								Well depth 312 ft.				
lī [ːːːːːX]							7 Cable tool Rotary Driven Dug					
						Hollow rod Jetted Bored _Z_ Reverse rotary						
							8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock					
11 1 ' 1 ' 1							Lawn Oil field water Other					
								9. Casing: Material _Step Height: Above 1 to w				
I S								RMP PVC Weight Solds./ft. Dia. in. to Ft. depth Wall Thickness: inches or Dia. in. to Ft. depth gage No. 2 / 9 / M/NC				
	ile ————							Dia. 46 in. to 44 oft. dep	h Wall Thicknes	is: inches or		
5. Type and color of	material					From	То	10. Screen: Manufacturer's n	ame			
								Johnson Wivis:	ion			
								Slot/gauze_7 00	Length 201			
								Set between 277-297 Perf 230-277ft. a	ft, and	ft.		
								Gravel pack? ves Size rai				
								11. Static water level:	•	mo./day/yr.		
							\neg	ft. below land sur				
								12. Pumping level below land 290 ft. after 3 h	rs. pumping00	g.p.m.		
								ft. after h	700 mping —	g.p.m.		
								Estimated maximum yield 13. Water sample submitted:		mo./day/yr.		
								Yes <u>X No</u>	Date	****		
								14. Well head completion: Pitless adapter	12 Inches at	bove grade		
	And an all the section (100 days)							15. Well grouted? Yes		3.445	12	
								With: Neat cement		Concrete .	¬ [
								Depth: From ft. to . 16. Nearest source of possible		N/A	1	
								ft Direction	Туре .			
	,							Well disinfected upon comple 17. Pump:	X Not instal			
								Manufacturer's name			<u></u>	
								Model number	HP	1	(g) "	
								Type:	— п. сарасту –	g.p.m.	9	
								Submersible		urbine eciprocating	N	
	(Use a second sl	eet if neede	d)					Centrifugal		ther	» (/)	
18. Elevation:	19. Remarks:							20. Water well contractor's o			1/2	
								This well was drilled under my is true to the best of my know	•		51.	
Topography:								Minter Wikson Drilling 208				
Business name Box Address O Box								Address Box A	Garden City, KS.			
Upland							٩	8ighad Authorized repr	to Keyen	9. 22	E.W	
Valley								Authorized rep	esenidive	· i	J.	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

Trans (1940) . P.O. Ber 195 . GARDEN CITY TANKS COM

.

Consider the Special Control of the Control of the

Status Taxas Level : 120'

lest il

300	****	
9.0	2	Top Sall
	41	Brown Stud & Clay, Bond, Back, Stud
	100000	Rife to Sec, Sand & direct parters.
74	A CONTRACT OF THE PARTY OF THE	Brown Sandy Clay Fine To Ned. Sand & Gravel
		Brown Sandy Clay
1000	10 miles 10	Fine To Med. Sand & Grayel
		Light Brown Saudy Clay
126	148	Fine To Med. Sand & Cravel, Tight
	157	
		-Pine To Med. Sand & Gravel, Tight
185	No. 17 Year of the Control of the Co	Fine To Med. Sand & Gravel Mixed White Rock
200		Brown Sandy Clay
216	244	Fine To Med. Sand & Gravel Brown Sandy Clay
244		Fine To Med. Sand & Gravel, Loose
	260	Brown Sandy Clay
The state of the s	265	Fine To Med. Sand & Gravel
265	272	Bucom Sand, Clay, Grovel Streak
	201	Fine To Med. Sand a Gravel, Tight
	290	Yellow Clay, Brown ock, Hard
290	326	Yellow, Sed Clay, Brown Rock, Hard