


1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 NW 1/4 Section Number 27 Township Number T 24 S Range Number R 38 E/W
 County: Kearny

Distance and direction from nearest town or city street address of well if located within city?

11-3/4 miles west of Lakin, Ks.

2 WATER WELL OWNER: Lena Swank c/o Norman Swank
 RR#, St. Address, Box # : Hwy. 50 West 12 Mile Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Lakin, Ks. 67860 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 1 ft. 2. 82 ft. 3. 19 ft.
 WELL'S STATIC WATER LEVEL 82 ft. below land surface measured on mo/day/yr 2-19-92
 Pump test data: Well water was 8 ft. after 10 hours pumping 130 gpm
 Est. Yield 8 gpm: Well water was 10 ft. after 130 hours pumping 130 gpm
 Bore Hole Diameter 10 in. to 130 ft., and 130 in. to 130 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well stock
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 XPVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 130 ft., Dia 130 in. to 130 ft., Dia 130 in. to 130 ft.
 Casing height above land surface 12 in., weight 200 lbs./ft. Wall thickness or gauge No. 200 psi
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass XPVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 10
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped X Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 10
 SCREEN-PERFORATED INTERVALS: From 101 ft. to 130 ft., From 101 ft. to 130 ft.
 GRAVEL PACK INTERVALS: From 101 ft. to 130 ft., From 101 ft. to 130 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite hole plug seal Other plug seal
 Grout Intervals: From 0 ft. to 20 ft., From 65 ft. to 65 ft., From 65 ft. to 65 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy X Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? 500 How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	top soil			
1	61	fine to medium & coarse sand			
61	72	brown clay			
72	81	coarse sand			
81	112	brown clay, few sand streaks			
112	118	brown clay			
118	122	medium & coarse sand			
122	129	yellow clay, some broken rock			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-19-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 532 This Water Well Record was completed on (mo/day/yr) 2-24-92
 under the business name of Midwest Well & Pump by (signature) Victor Jankef

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.