

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

T R EW sec 1/4 1/4 1/4 No.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

N 1/2 SE 1/4 SE 1/4

1 Location of well: County HAMILTON Township name \_\_\_\_\_ Fraction SE 1/4 Section number 14 Town number 24 Range number 39

Distance and direction from nearest town or city: \_\_\_\_\_ 3 Owner of well: Bob Taylor  
Street address of well location if in city: \_\_\_\_\_ Address: Syracuse 67878

Locate with "X" in section below: Sketch map:  
N  
W E  
S  
1 Mile

4 Well depth: 255 ft. Date of completion 5-12-77  
Well diameter 2 7/8 in.  
5  Cable tool  Rotary  Driven  Dug  
 Hollow rod  Jetted  Bored  Reverse rotary  
6 Use:  Domestic  Public supply  Industry  
 Irrigation  Air conditioning  Commercial  
 Test well  
7 Casing: Material PVC Height: above/below  
Threaded  Welded  Surface 24 in.  
Diam. \_\_\_\_\_ Weight \_\_\_\_\_ lbs./ft. \_\_\_\_\_  
5 in. to 255 ft. depth Drive shoe?  Yes  No  
\_\_\_\_\_ in. to \_\_\_\_\_ ft. depth

| 2 | Type and color of material | From       | To         |
|---|----------------------------|------------|------------|
|   | <u>Overburden 3/4 Clay</u> | <u>0</u>   | <u>19</u>  |
|   | <u>Blue Shale</u>          | <u>19</u>  | <u>180</u> |
|   | <u>Dakota Sand</u>         | <u>180</u> | <u>255</u> |
|   |                            |            |            |
|   |                            |            |            |
|   |                            |            |            |
|   |                            |            |            |
|   |                            |            |            |
|   |                            |            |            |
|   |                            |            |            |

8 Screen:  
Manufacturer S31  
Type PVC Dia. 5  
Slot/gauze 5/32 Length 75'  
Set between 80 ft. and 255 ft.  
Fittings:  
Gravel pack  Yes  No Size range of material 3/4

9 Static water level:  
180 ft. below land surface Date 5-12-77

10 Pumping level below land surfaces:  
\_\_\_\_\_ ft. after \_\_\_\_\_ hrs. pumping \_\_\_\_\_ g.p.m.  
\_\_\_\_\_ ft. after \_\_\_\_\_ hrs. pumping \_\_\_\_\_ g.p.m.  
Estimated maximum yield 15 g.p.m.

11 Water sample submitted:  
 Yes  No Date \_\_\_\_\_

12 Well head completion:  
 Pitless adapter 24 inches above grade

13 Well grouted?  Yes  No  
 Neat cement  Bentonite   
Depth: From 0 ft. to 12 ft.

14 Nearest source of possible contamination:  
ft. \_\_\_\_\_ Direction \_\_\_\_\_ Type \_\_\_\_\_  
Well disinfected upon completion?  Yes  No

15 Pump:  Not installed  
Manufacturer's name \_\_\_\_\_  
Model number \_\_\_\_\_ HP \_\_\_\_\_ Volts \_\_\_\_\_  
Length of drop pipe \_\_\_\_\_ ft. capacity \_\_\_\_\_ g.m.p.  
Type:  
 Submersible  Turbine  
 Jet  Reciprocating  
 Centrifugal  Other

16 Remarks: elevation  
pasture well

Topography:  
 Hill  
 Slope  
 Upland  
 Valley

17 Water well contractor's certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Eaton Drilling 300  
Business name \_\_\_\_\_ License No. \_\_\_\_\_  
Address Syracuse  
Signed [Signature] Date 5-12-77

24 39 W 14 N 1/2 SE SE