WATER WELL RECORD Division of Water Resources App. No. Form WWC-5 1 LOCATION OF WATER WELL: Fraction Section Number Township No. Range Number County: Reno NW 1/4 NW 1/4 NE 1/4 NW 1/4 24 S Street/Rural Address of Well Location: if unknown, distance & direction Global Positioning System (GPS) information: Latitude: .37,98499 (in decimal degrees) from nearest town or intersection: If at owner's address, check here Longitude: 097.77045 (in decimal degrees) From 50 Hwy. & Haven Rd. 3S 1/4E SSR Elevation: 1473 Datum: ☐ WGS 84, ☐ NAD 83, **②** NAD 27 WATER WELL OWNER: John Hansen Collection Method: GPS unit (Make/Model: Garmin csx RR#, Street Address, Box #: 613 Thunderbird City, State, ZIP Code Digital Map/Photo, I Topographic Map, Land Survey McPherson, Kansas 67460 Est. Accuracy: <a></a> <3 m, <a></a> 3-5 m, <a></a> 5-15 m, <a></a> <a>>15 m</a> LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 39 ft. SECTION BOX: Pump test data: Well water was......ft. after...... hours pumping...... gpm EST. YIELD......gpm. Well water was......ft. after...... hours pumping..........gpm -- NE -Bore Hole Diameter 30 in. to 39 ft., and in. to ft. w WELL WATER TO BE USED AS: Public water supply ☐ Injection well ☐ Geothermal Oil field water supply ☐ Dewatering ☐ Feedlot Other (Specify below) - SW - --- SE -☐ Domestic-lawn & garden ☐ Monitoring well **✓** Irrigation ☐ Industrial Was a chemical/bacteriological sample submitted to Department? 

Yes No S If ves, mo/day/vr sample was submitted..... -----1 mile-----Water well disinfected? Yes No 5 TYPE OF CASING USED: Steel PVC PVC ☐ Other ..... CASING JOINTS: Glued Clamped Welded Threaded
Casing diameter 16 in to 29 ft., Diameter in to ft.
Casing height above land surface 36 in., Weight SCH 40 lbs/ft., Wall thickness or gauge No ...500 TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Stainless Steel☐ Galvanized Steel PVC None used (open hole) ☐ Steel Other (Specify) Brass SCREEN OR PERFORATION OPENINGS ARE: ☐ Gauze wrapped ☐ Torch cut ☐ Continuous slot ☐ Mill slot ☐ Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 29 ft. to 39 ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other..... From 17 ft. to 0 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: Septic tank ☐ Lateral lines ☐ Pit privy Other (specify below) Livestock pens ☐ Insecticide storage Cesspool Sewage lagoon Fuel storage Sewer lines Abandoned water well irrigation well Fertilizer storage Oil well/gas well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard Direction from well South Distance from well ...300'..... FROM TO LITHOLOGIC LOG FROM TO LITHO, LOG (cont.) or PLUGGING INTERVALS 0 Top soil 6 Brown clay 39 Medium sand and gravel 39 40 Yellow clay 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, or plugged under my jurisdiction and was completed on (mo/day/year) .5-3-2012...... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. .134...... This Water Well Record was completed on (mo/day/year) 5-11-2012...... under the business name of Rosencrantz-Bemis Ent. by (signature) by (signature) Rosencrantz-Bemis Ent. INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.

KSA 82a-1212

47,771

Check: White Copy, Blue Copy, Pink Copy