

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: Reno		SE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$		14		T 24 S		R 4W E/W	
Distance and direction from nearest town or city? 1 West Elmer, 3/4 south, 1000' East					Street address of well if located within city?				

2 WATER WELL OWNER:		Amoco Oil Co.		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		RFD 2		Application Number:	
City, State, ZIP Code :		Hutchinson, KS 67501 # 19			

3 DEPTH OF COMPLETED WELL		40 ft. Bore Hole Diameter		6 in. to 40 ft., and in. to	
Well Water to be used as:		5 Public water supply		8 Air conditioning	
1 Domestic 3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation 4 Industrial		7 Lawn and garden only		11 Injection well	
		XX Observation well		12 Other (Specify below)	
Well's static water level		15 ft. below land surface measured on		10 month 3 day 1980 year	
Pump Test Data		Well water was		ft. after	
Est. Yield		gpm: Well water was		ft. after	

4 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		Casing Joints: Glued		Clamped	
XX Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)		Welded	
2 PVC		4 ABS		7 Fiberglass				Threaded XX	
Blank casing dia		4 in. to 0 ft. Dia		4 in. to 10 ft. Dia		in. to		ft.	
Casing height above land surface		24 in. weight		2 lbs./ft. Wall thickness or gauge No		216			
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
Screen or Perforation Openings Are:		5 Gauzed wrapped		XX Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
Screen-Perforation Dia		4 in. to 10 ft. Dia		XX 4 in. to 40 ft. Dia		in. to		ft.	
Screen-Perforated Intervals:		From 10 ft. to 40 ft.		From		ft. to		ft.	
Gravel Pack Intervals:		From 10 ft. to 40 ft.		From		ft. to		ft.	

GROUT MATERIAL:		1 Neat cement		XX Cement grout		3 Bentonite		4 Other	
Grouted Intervals: From		0 ft. to 10 ft.		From		ft. to		ft.	
What is the nearest source of possible contamination:		1 Septic tank		4 Cess pool		7 Sewage lagoon		10 Fuel storage	
2 Sewer lines		5 Seepage pit		8 Feed yard		11 Fertilizer storage		14 Abandoned water well	
3 Lateral lines		6 Pit privy		9 Livestock pens		12 Insecticide storage		15 Oil well/Gas well	
						13 Watertight sewer lines		16 Other (specify below)	
Direction from well		How many feet		?		Water Well Disinfected? Yes		No	
Was a chemical/bacteriological sample submitted to Department? Yes		No		X		If yes, date sample			
was submitted		month		day		year		Pump Installed? Yes	
						No		X	
If Yes: Pump Manufacturer's name		Model No.		HP		Volts			
Depth of Pump Intake		ft.		Pumps Capacity rated at		gal./min.			
Type of pump:		1 Submersible		2 Turbine		3 Jet		4 Centrifugal	
		5 Reciprocating		6 Other					

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was XX constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 10 month 3 day 1980 year	
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134	
This Water Well Record was completed on 10 month 6 day 1980 year under the business name of Rosencrantz-Bemis by (signature) Mike Hawes	

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
	0	3	Top Soil			
	3	9	Clay			
	9	40	Medium Sand			

ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

OFFICE USE ONLY

T

24

R

4

SEC

14

SE 1/4

SE 1/4

NW 1/4