


1 LOCATION OF WATER WELL: County: HAMILTON Fraction: NE 1/4 NE 1/4 SW 1/4 Section Number: 7 Township Number: T 24 S Range Number: R 40 E/W

Distance and direction from nearest town or city street address of well if located within city?
200 SOUTH MAIN, SYRACUSE, KANSAS 67878

2 WATER WELL OWNER: Syracuse Cooperative Exchange
 RR#, St. Address, Box #: P.O. Box 946 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Syracuse, Kansas 67878 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 25.0 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 17 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL: 17.28 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter: 8.25 in. to . ft., and . in. to . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 0 Monitoring well #4
 Was a chemical/bacteriological sample submitted to Department? Yes . No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes . No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped .
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded .
 7 Fiberglass Threaded.
 Blank casing diameter: 2 in. to 15 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface: 0 in., weight . lbs./ft. Wall thickness or gauge No. 3CH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) .
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) .
 SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 25 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .
 Grout Intervals: From 15 ft. to 13 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? NE How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1.0</u>	<u>Concrete Pavement</u>			
<u>1.0</u>	<u>3.0</u>	<u>Silt; DK BEDDN, CLAYEY w/ pebbles</u>			
<u>3.0</u>	<u>10.0</u>	<u>CLAY; GR BEDDN</u>			
<u>10.0</u>	<u>11.5</u>	<u>SAND; BROWN, FINE GR</u>			
<u>11.5</u>	<u>12.5</u>	<u>CLAY; GR BROWN.</u>			
<u>12.5</u>	<u>14.5</u>	<u>SAND; GR BROWN, FINE TO MED GR</u>			
<u>14.5</u>	<u>25.0</u>	<u>SAND & GRAVEL</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/10/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 331 This Water Well Record was completed on (mo/day/yr) 06/22/92 under the business name of Hydrochemical Services Inc. by (signature) Daniel Hilde Wallace