

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.


Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Hamilton Fraction SW 1/4 SE 1/4 SW 1/4 NE 1/4 Section Number 25 Township Number T 24 S Range Number R 41 E W

2 WELL OWNER: Last Name: Pollart First: Andy Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: X

3 LOCATE WELL WITH "X" IN SECTION BOX: N W E S



4 DEPTH OF COMPLETED WELL: 360 ft. Depth(s) Groundwater Encountered: 1) 158 ft. 2) ... 3) ... 4) Dry Well WELL'S STATIC WATER LEVEL: 156 ft. below land surface, measured on (mo-day-yr) 08/23/2018

5 Latitude: 37.935821 (decimal degrees) Longitude: 101.768292 (decimal degrees) Datum: X WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model: ... (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper

6 Elevation: 3291 ft. X Ground Level Topographic Map Source: Land Survey GPS Topographic Map X Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: X Household Lawn & Garden Livestock 2. Irrigation 3. Feedlot 4. Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No X If yes, date sample was submitted: Water well disinfected? Yes No X

8 TYPE OF CASING USED: Steel PVC X Other CASING JOINTS: Glued Clamped X Welded Threaded Casing diameter 6 in. to 360 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in. Weight lbs./ft. Wall thickness or gauge No. SDR17

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC X Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped X Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 160 ft. to 240 ft., From 320 ft. to 360 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 35 ft. to 360 ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite X Other Grout Intervals: From 5 ft. to 35 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage X Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? East Distance from well? 150 ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a 'Notes' section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 08/23/2018 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 08/31/2018 under the business name of Nash Water Well Service, LLC

Hamilton

SW SE SW NE

25-24-41W

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Andy Pollart
Doc ID	1420135

Litholgy

0	37	FINE MEDIUM SAND
37	46	TAN CLAY/FINE SAND LAYERS
46	54	FINE COARSE SAND, THIN ROCK LAYERS
54	72	FINE COARSE SAND/ SMALL GRAVEL STREAKS
72	158	BLUE SHALE
158	165	BLUE CLAY, GRAY SANDSTONE
165	220	GRAY SANDSTONE WITH GRAY CLAY
220	290	GRAY CLAY WITH GRAY SANDSTONE STREAKS
290	300	BLUE SHALE AND GRAY CLAY WITH GRAY SANDSTONE STREAKS
300	345	BLUE CLAY WITH GRAY SANDSTONE STREAKS
345	356	BLUE SHALE