

Well #3

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

45937


Well ID

- Original Record, Correction, Change in Well Use

1 LOCATION OF WATER WELL: County: Hamilton, Fraction SW 1/4 NE 1/4 SE 1/4 NE 1/4, Section Number 36, Township Number T 24 S, Range Number R 41 E W

2 WELL OWNER: Last Name: Fullmer, First: Auto Company, Street or Rural Address: 3 1/2 Miles South of Syracuse on Hwy 27 West 500'

3 LOCATE WELL WITH "X" IN SECTION BOX: N, W, E, S



4 DEPTH OF COMPLETED WELL: 360 ft. Depth(s) Groundwater Encountered: 1) 271 ft., 2) ... ft., 3) ... ft., or 4) Dry Well. WELL'S STATIC WATER LEVEL: 271 ft. below land surface, measured on (mo-day-yr) 09/17/2019.

5 Latitude: 37.923317 (decimal degrees), Longitude: 101.763377 (decimal degrees), Datum: WGS 84, Source for Latitude/Longitude: GPS (unit make/model: ...)

6 Elevation: 3299 ft. Ground Level, TOC, Source: Land Survey, GPS, Topographic Map, Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household, Lawn & Garden, Livestock, Irrigation, Feedlot, Industrial. 5. Public Water Supply, 6. Dewatering, 7. Aquifer Recharge, 8. Monitoring, 9. Environmental Remediation, 10. Oil Field Water Supply, 11. Test Hole, 12. Geothermal, 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? No. Water well disinfected? Yes

8 TYPE OF CASING USED: Steel, PVC, Other. CASING JOINTS: Glued, Clamped, Welded, Threaded. Casing diameter: 8 in. to 360 ft., Diameter: ... in. to ... ft., Casing height above land surface: 24 in., Weight: ... lbs./ft., Wall thickness or gauge No. SDR17.

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel, Stainless Steel, Brass, Galvanized Steel, PVC, Other (Specify):

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot, Mill Slot, Gauze Wrapped, Torch Cut, Drilled Holes, Other (Specify), Louvered Shutter, Key Punched, Wire Wrapped, Saw Cut, None (Open Hole). SCREEN-PERFORATED INTERVALS: From 180 ft. to 360 ft., From ... ft. to ... ft., GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 50 ft. to 360 ft., From ... ft. to ... ft.

9 GROUT MATERIAL: Neat cement, Cement grout, Bentonite, Other. Grout Intervals: From 5 ft. to 50 ft., From ... ft. to ... ft., From ... ft. to ... ft.

Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank, Lateral Lines, Pit Privy, Livestock Pens, Insecticide Storage, Sewer Lines, Cess Pool, Sewage Lagoon, Fuel Storage, Abandoned Water Well, Watertight Sewer Lines, Seepage Pit, Feedyard, Fertilizer Storage, Oil Well/Gas Well, Other (Specify) SEWER EAST. 200'. LAGOON. NORTH. 300'. FEED

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 09/17/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846. This Water Well Record was completed on (mo-day-year) 09/27/2019 under the business name of Nash Water Well Service, LLC.

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	
Doc ID	1472785

Litholgy

0	15	FINE MEDIUM SAND
15	48	FINE COARSE SAND WITH SMALL TO LARGE GRAVEL
48	75	TAN CLAY FINE MEDIUM SAND
75	140	BLUE SHALE
140	180	GRAY CLAY WITH GRAY SANDSTONE STREAKS
180	200	GRAY SANDSTONE WITH GRAY CLAY STREAKS
200	220	GRAY SANDSTONE WITH GRAY CLAY
220	240	GRAY SANDSTONE WITH GRAY CLAY
240	260	GRAY GLAY WITH SANDSTONE STREAKS
260	340	GRAY SANDSTONE WITH GRAY CLAY STREAKS
340	350	GRAY SANDSTONE BLUE SHALE
350	368	BLUE SHALE