

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

45937

Well ID

Well 1

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Hamilton Fraction NE 1/4 SW 1/4 SE 1/4 NE 1/4 Section Number 36 Township Number T 24 S Range Number R 41 E W

2 WELL OWNER: Last Name: Business: Fullmer Auto Company Texas LLC Address: PO Box 986 City: Syracuse State: KS ZIP: 67878 Street or Rural Address where well is located: Syracuse South 3 1/2 mile on Hwy 27 West 800'

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S 1 mile

4 DEPTH OF COMPLETED WELL: 360 ft. Depth(s) Groundwater Encountered: 1) 274 ft. 2) ft. 3) ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 274 ft. below land surface, measured on (mo-day-yr) 09/11/2019

5 Latitude: 37.922602 (decimal degrees) Longitude: 101.764462 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model) (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper

6 Elevation: 3303 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 8 in. to 360 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 18 in. Weight lbs./ft. Wall thickness or gauge No. SDR17 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 220 ft. to 360 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 50 ft. to 360 ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 5 ft. to 50 ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? WEST Distance from well? 100 ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-yr) 09/11/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-yr) 09/27/2019 under the business name of Nash Water Well Service, LLC

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	
Doc ID	1472778

Litholgy

0	30	FINE COARSE SAND
30	45	FINE COARSE SAND WITH SMALL TO LARGE COBBLE
45	50	FINE COARSE SAND WITH TAN CLAY STREAKS
50	60	TAN BROWN CLAY WITH FINE SAND STREAKS
60	73	TAN CLAY WITH FINE SAND
73	104	BLUE SHALE
104	109	ROCK HARD
109	135	BLUE SHALE WITH ROCK LAYERS
135	143	GRAY CLAY
143	260	GRAY CLAY WITH THIN GRAY SANDSTONE STREAKS
260	340	GRAY SANDSTONE WITH GRAY CLAY STREAKS
340	350	GRAY SANDSTONE WITH BLUE SHALE STREAKS
350	365	BLUE SHALE