WATE	R WE	LL RECORD Form V	VWC-5	Division of Water Resources App. No.	
		NOF WATER WELL: Fraction		Section Number Township No. Range Number	
Cou	nty: Re	no SE ¼ NW ¼ N	W 1/4 SW 1/4	19 T 24 S R 5 □E 🗗 W	
		Address of Well Location; if unknown, distance		Global Positioning System (GPS) information:	
from nearest town or intersection: If at owner's address, check here .			Latitude: 37.94726 (in decimal degrees)		
				Longitude: 097.91965 (in decimal degrees)	
				Elevation: 1535 Datum: WGS 84, NAD 83, NAD 27	
2 WA	TER W	ELL OWNER: Vernon Bontrager		Collection Method:	
RR#, Street Address, Box #: 875 South Sand Creek Road			GPS unit (Make/Model: Garnin csx)		
City	, State, Z	ZIP Code : Hutchinson, Kansas 6750		Digital Map/Photo, Topographic Map, Land Survey	
Est. Accuracy:					
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 57					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
	N WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr. 11-09-10				
Pump test data: Well water wasft. after hours pumping					
EST. YIELDgpm. Well water was					
W E Bore Hole Diameter 4.9					
-	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
	S If yes, mo/day/yr sample was submitted				
	l mile				
5 TYPE OF CASING USED: Steel V PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter 16. in. to .37. ft., Diameter in. to ft., Diameter in. to ft.					
Casing height above land surface 18 in., Weight SCH 40 lbs./ft., Wall thickness or gauge No500					
TYPE	TYPE OF SCREEN OR PERFORATION MATERIAL:				
Steel Stainless Steel PVC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREE	EN-PERI			ft., From ft. to ft.	
	CDAN	From	. ft. to	ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 57 ft. to 20 ft., From ft. to ft. From ft. to ft. ft.					
6 CROUT MATERIAL: Nest cement Cement grout P Rentonite O Other 100 Soil					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other top soil Grout Intervals: From 20 ft. to 2 ft., From 2 ft. to 0 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
	Septic ta	ank	Livestock j	· <u> </u>	
	Sewer li				
		ght sewer lines Seepage pit Feedyard m well	Fertilizer s	torage Oil well/gas well NONE from well	
FROM	TO	LITHOLOGIC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0	3	Top soil		57 Tan clay	
3	15	Brown clay	1	- Turnotay	
15	25	Tan clay tight-fine sand 80/20			
25	27	Tan clay & fine sand w/few pcs.			
		of hard caliche			
27	30	Tan clay & fine sand 80/20			
30	47	Small sand			
47	48	Clay yellowish tan			
48	54	Small sand & yellowish tan clay	 		
mix 70/30					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, or plugged under my jurisdiction and was completed on (mo/day/year) .11-9-10					
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 11-19-10					
under the business name of Rosencrantz-Bemis Ent. by (signature D.) Dadasas					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy					

Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy