

WATER WELL RECORD				Form WWC-5				KSA 82a-1212 PLUGGING REPORT			
1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Renb</u>		<u>SE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$		<u>7</u>		<u>T 24</u> <u>S</u>		<u>R 5</u> <u>W</u>			
Distance and direction from nearest town or city street address of well if located within city? <u>2 1/2 mi. N. of Yoder 2 1/2 W.</u>											
2 WATER WELL OWNER: <u>Rutus W. Yoder</u>											
RR#, St. Address, Box #: <u>Box 101</u>											
City, State, ZIP Code: <u>Yoder, KS 67585</u>											
Board of Agriculture, Division of Water Resources											
Application Number: <u>38221</u>											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>150</u> ft.		ELEVATION:							
		Depth(s) Groundwater Encountered: <u>1</u> <u>34</u> ft.		ft. 2:		ft. 3:		ft.			
		WELL'S STATIC WATER LEVEL: <u>27</u> ft. below land surface measured on mo/day/yr <u>12/29/75</u>									
		Pump test data: Well water was		ft. after		hours pumping		gpm			
		Est. Yield		gpm: Well water was		ft. after		hours pumping			
		Bore Hole Diameter:		in. to		ft., and		in. to			
		WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well			
		1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering			
		2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes		No		If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes		No							
5 TYPE OF BLANK CASING USED:											
1 Steel											
3 RMP (SR)											
X6 Asbestos-Cement											
9 Other (specify below)											
4 ABS											
7 Fiberglass											
CASING JOINTS: Glued											
Clamped											
Welded											
Threaded											
Blank casing diameter: <u>16</u> in. to <u>150</u> ft., Dia											
Casing height above land surface: <u>36</u> in., weight											
lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel											
3 Stainless steel											
5 Fiberglass											
8 RMP (SR)											
11 Other (specify)											
2 Brass											
4 Galvanized steel											
6 Concrete tile											
9 ABS											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
5 Gauzed wrapped											
8 Saw cut											
11 None (open hole)											
1 Continuous slot											
3 Mill slot											
6 Wire wrapped											
9 Drilled holes											
2 Louvered shutter											
4 Key punched											
7 Torch cut											
10 Other (specify)											
SCREEN-PERFORATED INTERVALS:											
From											
ft. to											
ft., From											
ft. to											
ft., From											
ft. to											
GRAVEL PACK INTERVALS:											
From											
ft. to											
ft., From											
ft. to											
ft., From											
ft. to											
6 GROUT MATERIAL:											
1 Neat cement											
X2 Cement grout											
X3 Bentonite Holeplug											
Loamy Clay											
Grout Intervals: (2) From <u>30</u> ft. to <u>29</u> ft.											
ft. (4) From <u>29</u> ft. to <u>6</u> ft.											
ft. (3) From <u>6</u> ft. to <u>3</u> ft.											
What is the nearest source of possible contamination: <u>None</u>											
1 Septic tank											
4 Lateral lines											
7 Pit privy											
10 Livestock pens											
14 Abandoned water well											
2 Sewer lines											
5 Cess pool											
8 Sewage lagoon											
11 Fuel storage											
15 Oil well/Gas well											
3 Watertight sewer lines											
6 Seepage pit											
9 Feedyard											
12 Fertilizer storage											
16 Other (specify below)											
13 Insecticide storage											
Direction from well?											
How many feet?											
FROM											
TO											
LITHOLOGIC LOG											
FROM											
TO											
PLUGGING INTERVALS											
150'											
30'											
Sand, Clean											
30'											
29'											
Grout, Cement											
29'											
6'											
Clay, Loamy											
6'											
3'											
Grout, Bentonite (Holeplug)											
3'											
0											
Topsoil, Clean											
The plugging interval from 6 ft to 0 was witnessed by Michael T. Dealy, Equus Beds Groundwater Management District No. 2											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was											
X1 constructed, X2 reconstructed, (3) plugged under my jurisdiction and was											
completed on (mo/day/year) <u>07/28/92</u>											
and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. <u>N/A</u>											
This Water Well Record was completed on (mo/day/yr) <u>07/28/92</u>											
under the business name of <u>N/A</u>											
by (signature) <u>Michael T. Dealy</u>											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											