

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>	<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>29</u>	T <u>24</u> S	R <u>5</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

1.5 miles West, 1 mile south of YoderMW-3

2 WATER WELL OWNER: <u>Deluxe Specialties Mfg. Co.</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>P.O. Box 879</u>	Application Number:
City, State, ZIP Code: <u>Hutchinson, KS 67504</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>34</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>19</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>19</u> ft. below land surface measured on mo/day/yr <u>4-18-89</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter <u>12</u> in. to <u>34</u> ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No <u>X</u>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>	7 Fiberglass		Threaded <u>X</u>
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>4</u> in. to <u>19</u> ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface <u>36</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sc 440</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>2 Mill slot</u>	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From <u>19</u> ft. to <u>34</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>34</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals: From <u>surface</u> ft. to <u>10</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<u>16 Other (specify below)</u>
			13 Insecticide storage	<u>solvent storage</u>
Direction from well? <u>South</u>			How many feet? <u>60</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>19</u>	<u>brown, silty CLAY</u>			
<u>19</u>	<u>22</u>	<u>brown, sandy CLAY</u>			
<u>22</u>	<u>34</u>	<u>brown, silty SAND, med to fine grained</u>			
Note Grout is from Surface to 10'; OK by Darrel Plummer 2-21-89					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-18-89</u> and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. <u>496</u> This Water Well Record was completed on (mo/day/yr) <u>5/19/89</u>
under the business name of <u>Groundwater Tech R</u> by (signature) <u>Darrel Plummer</u>