

1 LOCATION OF WATER WELL: County: <u>Reno</u>	Fraction <u>NW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>29</u>	Township Number <u>T 24 S</u>	Range Number <u>R 5 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 mile south and 1 1/2 miles West of Yoder

2 WATER WELL OWNER: <u>Deluxe Specialties Mfg. Co.</u>	<u>MW-5</u>
RR#, St. Address, Box #: <u>P.O. Box 879</u>	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: <u>Hutchinson, KS 67504</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>40</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>21</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>21</u> ft. below land surface measured on mo/day/yr <u>2-6-90</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>7.25</u> in. to <u>40</u> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>2</u> in. to <u>32</u> ft. Dia			Threaded <u>X</u>
Casing height above land surface <u>36</u> in., weight			lbs./ft. Wall thickness or gauge No. <u>56 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	5 Mill slot	6 Wire wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	7 Torch cut	11 None (open hole)
SCREEN-PERFORATED INTERVALS:			
From <u>32</u> ft. to <u>40</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>18</u> ft. to <u>40</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS:	From <u>surface</u> ft. to <u>15</u> ft.	From <u>15</u> ft. to <u>18</u> ft.		
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>solvent storage</u>
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Brown, silty clay			
20	38	Light reddish brown clayey fine to coarse sand			
38	40	Gray, green weathered shale			
Grout variance granted					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-6-90</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>513</u> This Water Well Record was completed on (mo/day/yr) <u>3/28/90</u> under the business name of <u>Bangor and Groundwater Tech. Inc.</u> by (signature) <u>Bangor and</u>
--