

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SW 1/4 NW 1/4 SW 1/4</u>	<u>35</u>	T <u>24</u> S	R <u>5</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 mi E 1 3/4 S of Yoder</u>					
2 WATER WELL OWNER: <u>Floyd Fry</u>					
RR#, St. Address, Box # : <u>Rt 2</u>					
City, State, ZIP Code : <u>Haven</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>90</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>14</u> ft. below land surface measured on mo/day/yr <u>7-6-89</u>			
		Pump test data: Well water was <u>85</u> ft. after <u>1</u> hours pumping <u>3</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>90</u> ft. and <u>5 1/2</u> in. to <u>117</u> ft.			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
(1) Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Stock</u>					
Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter <u>5</u> in. to <u>50</u> ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped (8) Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>50</u> ft. to <u>90</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>40</u> ft. From <u>45</u> ft. to <u>117</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3) Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft. From <u>40</u> ft. to <u>45</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy (10) Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? <u>W</u> How many feet? <u>100</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	BK Top Soil			
6	9	Gr Clay			
9	74	Br Clay			
74	90	Gr Rocky Clay			
90	117	Br Clay			
117	118	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-6-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>12-20-89</u> under the business name of <u>Miller Drilling</u> by (signature) <u>Eg mills</u>					