		WAT	ER WELL RECORD	Form WWC-5	KSA 82a-			
LOCATION OF		Fraction			n Number	Township N		Range Number
ounty: Reno		Near 1	4Center 4 SE	1/4	5	т 24	S	R 5 @ W
istance and direc	tion from nearest to	wn or city street	address of well if locate	d within city?				
2 miles S	outh & 2 m	iles Eas	t of South H	utchinsor	1			
WATER WELL	OWNER: C.E	3. Showal	ter					
R#, St. Address,	Box # : 880	3 E. Arl	ington Rd.				_	Division of Water Resource
ity, State, ZIP Co	^{de} : Hav	en. KS 6	7543					41,520
LOCATE WELL	S LOCATION WITH							· · · · · · · · · · · · · · · · · · ·
AN "X" IN SECT	N _	Depth(s) Groun	dwater Encountered	22	ft. 2		ft. 3	h
	1	WELL'S STATE	C WATER LEVEL	. 22 ft. bek	w land surf	ace measured or	n mo/day/yr	3-31-95
NW -	- NE	Pur	np test data: Well wat	er was	ft. af	ter	. hours pu	mping gpm
\w -	-							mping gpm
L i		Bore Hole Dian	neter30in. to	1.0.6.	ft., a	ınd	in	. to
w -	— — — ;	WELL WATER	TO BE USED AS:			8 Air conditioning		Injection well
. .		1 Domestic	3 Feedlot	6 Oil field water	supply	9 Dewatering	12	Other (Specify below)
sw -	·· · /	2 Irrigation	4 Industrial	7 Lawn and gar	den only 1	0 Monitoring we	II	
i		Was a chemica	l/bacteriological sample	submitted to Dep	artment? Ye	sΧ	; If yes	, mo/day/yr sample was su
	\$	mitted			Wat	er Well Disinfect	ed? Yes >	∑ No
TYPE OF BLAN	K CASING USED:		5 Wrought iron	8 Concrete	tile	CASING JC	INTS: Glue	dXClamped
1 Steel	3 RMP (\$	SR)	6 Asbestos-Cement	9 Other (sp	ecify below	')	Weld	ed
2 PVC	4 ABS		7 Fiberglass				Threa	aded
lank casing diame	eter 1.6	in. to66	ft., Dia	in. to		ft., Dia		in. to ft.
asing height above	e land surface	1.2	in., weight 1.	615	lbs./f	t. Wall thickness	or gauge N	lo . .5.0.0
	OR PERFORATION		•	7 PVC			bestos-ceme	
1 Steel	3 Stainles	ss steel	5 Fiberglass	8 RMP	_ (SR)	11 Ot	ner (specify)	
2 Brass	4 Galvan	ized steel	6 Concrete tile	9 ABS		12 No	ne used (op	pen hole)
CREEN OR PER	FORATION OPENI	NGS ARE:	5 Gauz	ed wrapped		8 Saw cut		11 None (open hole)
1 Continuous	slot 3 l	Mill slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered s	hutter 4 l	Key punched	7 Torcl	n cut		10 Other (specif	y)	
CREEN-PERFOR	ATED INTERVALS	: From	6.6 ft. to .	1.0.6	ft., Fron	n	ft. t	:o
		From	ft. to .		ft., Fron	n <i></i>	ft. 1	o
GRAVEL	PACK INTERVALS							:o
								o ft
GROUT MATER	RIAL: 1 Neat		2 Cement grout					
Grout Intervals:	From ()	. ft. to 2	0 ft., From	ft. to		ft., From .	. 	ft. to
Vhat is the neares	t source of possible	e contamination:	None within	1/4 mile	10 Livest	ock pens	14 A	bandoned water well
1 Septic tank	4 Late	eral lines	7 Pit privy		11 Fuel s	storage		il well/Gas well
2 Sewer lines	5 Ces	s pool	8 Sewage lag			zer storage		Other (specify below)
3 Watertight	sewer lines 6 See	-	9 Feedyard			icide storage		
Direction from well			•		How mar	•		
FROM TO		LITHOLOGIC	LOG	FROM	то		LUGGING I	NTERVALS
0 4	Top So	i.l						
4 17	Clay-Re							
17 22	Sand-Me	ed.						
22 35	Clay-Re	ed-Hard						
35 40								
40 51								
51 68		edWater	Loss					
68 79		uff-Limes						
79 10		edWater						
	1	-DIO CERTITIO		(1)			-1	
								der my jurisdiction and wa
ompleted on (mo/	uay/year) 3	-31-95		a	na this recoi	a is true to the b	est of my kn ムルノソク	owledge and belief. Kansa
			This Water V					/3
			gation Inc.		by (signat			uso
INSTRUCTIONS: U	se typewriter or ball poin	t pen. PLEASE PRESS	FIRMLY and PRINT clearly. P	ease fill in blanks, und	derline or circle	the correct answers.	Send top three	copies to Kansas Department