


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Reno	Fraction SE 1/4 SE 1/4 NE 1/4	Section number 5	Township number T 24 S	Range number R 6 W E/W
2. Distance and direction from nearest town or city: 3 1/2 W 1 1/2 S of S. Hutchinson, Ks.		3. Owner of well: John N. Mast Rt. 1 Hutchinson, Ks. 67501 City, state, zip code:			
4. Locate with "X" in section below: N 1 Mile W E S 1 Mile		Sketch map: 		6. Bore hole dia. 10 in. Completion date Well depth 52 ft. 10/14/76	
5. Type and color of material		From	To	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
topsoil		0	2	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
sandy soil brown		2	12	9. Casing: Material plst Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1.95 lbs./ft. Dia. 6 in. to 52 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .200	
clay yellow		12	18	10. Screen: Manufacturer's name J&L Type RMP Dia. 6" Slot/gauze 3/32 Length 10" Set between 42 ft. and 52 ft. ft. and 52 ft. Gravel pack? yes Size range of material F-1"	
sand coarse yellow		18	39	11. Static water level: 35 ft. below land surface Date 10/14/76 mo./day/yr.	
clay gray		39	41	12. Pumping level below land surfaces: 37 ft. after 1 hrs. pumping 20 g.p.m. ft. after 40 hrs. pumping 40 g.p.m. Estimated maximum yield 40 g.p.m.	
sand/some gravel yellow		41	52	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date	
				14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 12 inches above grade	
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 4 ft. to 14 ft.	
				16. Nearest source of possible contamination: ft. 70 Direction S Type septic Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
				17. Pump: Not installed Manufacturer's name Aermotor Model number SA1250 HP 1/2 Volts 230 Length of drop pipe 40 ft. capacity 12 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Miller Water Well Serv. 137 Business name Hutchinson, Ks. License No. Address 10/24/76 Signed John N. Mast Date 10/24/76 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5